

1" Round Recessed Oak™ Downlight

Small aperture 12V Downlight delivers over 600 lumens. More than a traditional 50W MR16 Halogen Lamp. Requires 12V AC Transformer (daisy chain up to 6). Dimmable MLV or ELV depending on transformer used.



Features

- IC Airtight for use with direct contact to insulation
- Height allows for use in 2 x 4 construction
- Daisy chain up to 6 fixtures with E1LDRV60
- 38° Standard beam with optional 28° and 60°
- Remodel requires no frame
- Wet Location Rated for Indoor and Outdoor Use
- JA8-1016-E, UL, and Energy Star Listed
- Life Span 50,000 Hours L70

Specifications

Wattage	6W
Lumens	600 lm - 675 lm
Voltage	12V
Color Temp.	2700K - 4000K
Dimmable	MLV/ELV
Lamp Type	LED
Beam Angle	28 - 60

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
E1L02F27W	LED	600 lm	2700K	6W	12V	MLV/ELV	38	White
E1L02F30W	LED	625 lm	3000K	6W	12V	MLV/ELV	38	White
E1L02F40W	LED	675 lm	4000K	6W	12V	MLV/ELV	38	White
E1L02F27B	LED	600 lm	2700K	6W	12V	MLV/ELV	38	Black
E1L02F30B	LED	625 lm	3000K	6W	12V	MLV/ELV	38	Black
E1L02F40B	LED	675 lm	4000K	6W	12V	MLV/ELV	38	Black
E1L02F27BZ	LED	600 lm	2700K	6W	12V	MLV/ELV	38	Bronze
E1L02N30BZ	LED	625 lm	3000K	6W	12V	MLV/ELV	28	Bronze
E1L02W40BZ	LED	675 lm	4000K	6W	12V	MLV/ELV	60	Bronze
E1L02F27H	LED	600 lm	2700K	6W	12V	MLV/ELV	38	Haze w/ White
E1L02F30H	LED	625 lm	3000K	6W	12V	MLV/ELV	38	Haze w/ White
E1L02F40H	LED	675 lm	4000K	6W	12V	MLV/ELV	38	Haze w/ White
E1L02F27BB	LED	600 lm	2700K	6W	12V	MLV/ELV	38	Black
E1L02F30BB	LED	625 lm	3000K	6W	12V	MLV/ELV	38	Black
E1L02F40BB	LED	675 lm	4000K	6W	12V	MLV/ELV	38	Black

Product Number Builder Example: E1L02F27W

1" Oak™ Downlight	Style	Beam Angle	Color Temperature	Finish
E1L	02 Round	F 38° N 28° W 60°	27 2700K 30 3000K 40 4000K	W White B Black w/ White Ring BZ Bronze H Haze w/ White Ring BB Black