

1" Round Recessed Oak™ Gimbal

Small aperture 12V Downlight delivers over 600 lumens. More than a traditional 50W MR16 Halogen Lamp. Requires 12V AC Transformer (daisy chain up to 6). Dimmable MLV or ELV depending on transformer used.



Features

- IC Airtight for use with direct contact to insulation
- Height allows for use in 2 x 4 construction
- Daisy chain up to 6 fixtures with E1LDRV60
- 38° Standard beam with optional 28° and 60°
- Remodel requires no frame
- Wet Location Rated for Indoor and Outdoor Use
- JA8-1016-E, UL, and Energy Star Listed
- Life Span 50,000 Hours L70

Specifications

Wattage	6W
Lumens	625 lm - 700 lm
Voltage	12V
Color Temp.	2700K - 4000K
Dimmable	MLV/ELV
Lamp Type	LED, LED
Beam Angle	38
CRI	93+

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
E1L32F27W	LED	625 lm	2700K	6W	12V	MLV/ELV	38	White
E1L32F30W	LED	650 lm	3000K	6W	12V	MLV/ELV	38	White
E1L32F40W	LED	700 lm	4000K	6W	12V	MLV/ELV	38	White
E1L32F27B	LED	625 lm	2700K	6W	12V	MLV/ELV	38	Black
E1L32F30B	LED	650 lm	3000K	6W	12V	MLV/ELV	38	Black
E1L32F40B	LED	700 lm	4000K	6W	12V	MLV/ELV	38	Black
E1L32F27BZ	LED	625 lm	2700K	6W	12V	MLV/ELV	38	Bronze

Product Number Builder Example: E1L32F27W

1" Oak™ Gimbal	Style	Beam Angle	Color Temperature	Finish
E1L	32 Round	F 38° N 28° W 60°	27 2700K 30 3000K 40 4000K	W White BZ Bronze BB Black