

# 1" Square Recessed Oak™ Gimbal

Small aperture 12V Downlight delivers over 600 lumens. More than a traditional 50W MR16 Halogen Lamp. Requires 12V AC Transformer (daisy chain up to 6). Dimmable MLV or ELV depending on transformer used.



## Features

- IC Airtight for use with direct contact to insulation
- Height allows for use in 2 x 4 construction
- Daisy chain up to 6 fixtures with E1LDRV60
- 38° Standard beam with optional 28° and 60°
- Remodel requires no frame
- Wet Location Rated for Indoor and Outdoor Use
- JA8-1016-E, UL, and Energy Star Listed
- Life Span 50,000 Hours L70

## Specifications

<b>Wattage</b>	6W
<b>Lumens</b>	625 lm - 700 lm
<b>Voltage</b>	12V
<b>Color Temp.</b>	2700K - 4000K
<b>Dimmable</b>	MLV/ELV
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	28 - 60

## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
<b>E1L22F27W</b>	LED	625 lm	2700K	6W	12V	MLV/ELV	38	White
<b>E1L22F30W</b>	LED	650 lm	3000K	6W	12V	MLV/ELV	38	White
<b>E1L22F40W</b>	LED	700 lm	4000K	6W	12V	MLV/ELV	38	White
<b>E1L22F27B</b>	LED	625 lm	2700K	6W	12V	MLV/ELV	38	Black w/ White
<b>E1L22F30B</b>	LED	650 lm	3000K	6W	12V	MLV/ELV	38	Black w/ White
<b>E1L22F40B</b>	LED	700 lm	4000K	6W	12V	MLV/ELV	38	Black w/ White
<b>E1L22F27BZ</b>	LED	625 lm	2700K	6W	12V	MLV/ELV	38	Bronze
<b>E1L22N30BZ</b>	LED	650 lm	3000K	6W	12V	MLV/ELV	28	Bronze
<b>E1L22W40BZ</b>	LED	700 lm	4000K	6W	12V	MLV/ELV	60	Bronze

## Product Number Builder Example: E1L22F27W

1" Oak™ Gimbal	Style	Beam Angle	Color Temperature	Finish
<b>E1L</b>	22 Square	<b>F</b> 38° <b>N</b> 28° <b>W</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K	<b>W</b> White <b>BZ</b> Bronze <b>BB</b> Black