

Fixture type:	Project name:		
Date:	Fixture type:		
Date.	Date:		

# 4" Airtight Smooth Cone Reflector Trim



#### **Features**

- Cone Reflector.
- Lamp: 75W MAX PAR30.
- O.D.: 5 1/16".

#### **Technical Details**

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

#### **Options**





Clear

White

#### **Product Numbers**

Item	Finish
EL901C	Clear
EL901W	All White

### Product Number Builder Example: EL901C

4" Cone Reflector Trim

Finish

**EL901** 

**C** Clear

**W** All White

# **Compatible** Products



For use with 4" Trims for PAR Lamps

# 4"Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction




4" Airtight IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket New Construction

	-			
FA.		-273D		
PIG.	100	=	-	

4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

## 4" Accessories



Fire Cover

Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%" \

CAT NO.	SPECIFICATIONS
FIRETAPE	<sup>3</sup> ⁄ <sub>4</sub> " W × 16' L