

# 4" LED IC Airtight Sloped Ceiling Remodel Housing - EL470RICA



## Features

- Allows for direct contact with insulation.
- California Title 24 (JA8-2016-E).

## Technical Details

### Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Housing adjusts to accommodate up to 3/4" ceiling thickness.
- Aluminum housing for greater heat dissipation.

**Installation:** Designed for ceiling plenums where 2x8 joists or taller are used. Template for hole cutout is provided with each housing. See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

**Electrical:** Connection is rated for 120V input.

**Compatible Housings:** EL470ICA, EL470RICA.

### Listings:


- UL Listed for Damp Location.
- UL Listed for Direct Contact with Insulation and Combustible Material.
- UL Listed for Feed Through.
- AirTight Per ASTM E-283.
- California Title 24 (JA8-2016-E).

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.

## Specifications

<b>Wattage</b>	14W
<b>Voltage</b>	120V
<b>Damp Location</b>	Listed

## Dimensions



## Product Numbers

Item	Watts	Voltage
EL470RICA	14W	120V