

# 4" LED Light Engine with Trimless Baffle

The perfect lighting solution for high-end residential and light commercial projects.



## Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 4" Cedar™ System Housings.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- Spackle frame included.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## Specifications

Wattage	12.88W
Lumens	1250 lm
Color Temp.	3500K
Lamp Type	LED
Beam Angle	60°
CRI	93+
Damp Location	Listed

## Options



All White



All Black



All Bronze

## Technical Details

**Optics:** Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Trim Construction:** Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.


**Installation:** Must be installed on a Cedar™ System housing with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.

### LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

**Sunset:** Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when

## Dimensions



## Spackle Frame Included



dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant.

## Product Number Builder

Example: **E434C0827W2**

ELCO 4" Trimless Baffle	Lumens	Color Temp.	Finish	Generation	Beam Angle
<b>E434C</b>	<div><b>08</b> 850 lm</div> <div><b>12</b> 1250 lm</div> <div><b>16</b> 1600 lm</div>	<div><b>27</b> 2700K</div> <div><b>30</b> 3000K</div> <div><b>35</b> 3500K</div> <div><b>40</b> 4000K</div> <div><b>50</b> 5000K</div> <div><b>SD</b> Sunset <sup>1</sup></div>	<div><b>W</b> All White</div> <div><b>BZ</b> All Bronze</div> <div><b>B</b> All Black</div>	<div><b>2</b> Gen 2</div> <div><b>1</b> Gen 1</div>	<div>60º lens</div> <div><b>-F</b> 38º lens</div> <div><b>-N</b> 24º lens</div> <div><b>-S</b> 15º lens</div>

<sup>1</sup> Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed