

Project name:
Fixture type:
Date:

4" Phenolic Step Baffle Trim



Features

- Phenolic Step, Metal Ring.
- Lamp: 32W MAX CFL (PL-T) or 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







All White

Black w/White Trim

All Bronze







All Nickel

All Black

Black w/Nickel Ring







White w/Nickel Trim

Nickel w/White Trim

Black w/Bronze Trim





Bronze w/White Trim

White w/Bronze

Product Numbers

Item	Finish
EL993B	Black with White Trim
EL993BZ	All Bronze
EL993W	All White
EL993N	All Nickel
EL993BB	All Black
EL993BN	Black with Nickel Trim
EL993WN	White with Nickel Trim
EL993NW	Nickel with White Trim
EL993BBZ	Black with Bronze Trim
EL993BZW	Bronze with White Trim
EL993WBZ	White with Bronze Trim

4" Phenolic Baffle Metal Trim		Finish
EL993		
	В	Black with White Trim
	ΒZ	All Bronze
	W	All White
	N	All Nickel
	ВВ	All Black
	BN	Black with Nickel Trim
	WN	White with Nickel Trim
	NW	Nickel with White Trim
	BBZ	Black with Bronze Trim
	BZW	Bronze with White Trim
	WBZ	White with Bronze Trim

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**



4" Airtight IC Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

4" Accessories



Fire Cover



Fire Enclosure

1
V)
9)

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 %" L x 14 %" W
FIREENCL-S	Shallow, 16" L x 14 %"

CAT NO.	SPECIFICATIONS
FIRETAPE	³ ⁄ ₄ " W × 16' L