

Proi	iect	name
	,	· · · · · · ·

Fixture type:

Date:

4" Reflector with Suspended Glass



Features

- · Reflector with Suspended Glass.
- Includes field changeable 3-optic lens (14°, 24°, 36°).
- O.D.: 4 7/8".

Technical Details

Construction:

- Meticulously manufactured trim with powder coated or anodized finish.
- · Diecast trim ring for durability and lasting quality.

Installation: Clips securely mount trim into housing and keeps ring flush with ceiling.

Housings: Compatible with ELD46ICA, ELDR46ICA.

Options



White


Product Numbers

Item	Beam Angle	Finish
EL4426W	14°, 24°, 36°	All White

Compatible Products



4" Integrated LED Housings



IC Airtight New Construction Housing

_	_	
CAT NO.	SPECIFICATIONS	
ELD47ICA	1200 lm/ 16W / 2700K	
ELD46ICA	1200 lm/ 16W / 3000K	
ELD45ICA	1200 lm/ 16W / 4000K	



Specifications

Beam Angle 14°, 24°, 36°

IC Airtight Remodel Housing

CAT NO.	SPECIFICATIONS
ELDR47ICA	1200 lm/ 16W / 2700K
ELDR46ICA	1200 lm/ 16W / 3000K
ELD45ICA	1200 lm/ 16W / 4000K