

Project name:	
Fixture type:	
Date:	

4" Shower Trim with Clear Lens



Features

- Shower Trim with Clear Lens.
- Lamp: 32W MAX CFL (PL-T) or 30W MAX R20.
- O.D.: 4 3/4"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



Finish

All Black

Item

EL911B

Product Number Builder Example: EL911BZ

4" Shower Trim with Clear Lens Finish

EL911

BZ All Bronze

B All Black

N Nickel

SH White Lexan

W All White

CP Copper

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**




4" Airtight IC Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	
EL99A	

SPECIFICATIONS	
Lamp: 50W MAX.	

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**

ra.	79	
P. C.		

4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS	
FL99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

4" Accessories



Fire Cover



Fire Enclosure



M	ica	Fi	re	Ta	pε

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3%"

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L