

# E.L.L. Module with 4" Square Baffle FLEXA™ Trim

E.L.L. Module with 4" FLEXA™ Square Baffle Trim, FLEXA™ is 2 pieces for maximum design flexibility. FLEXA™ trims are available in round, square as a reflector or baffle.



## Features

- Module with FLEXA™ twist and lock trim
- Smooth lens provides even lighting illumination
- ELL Module works in 4" & 6" housings with interchangeable trims.
- Twist-&-Lock System for easy trim installation.
- Excellent color rendering 93+ CRI.
- ENERGY STAR® Certified.
- Title 24 JA8 2016-E registered.
- Smooth and even dimming.
- Life span of 50,000 hours L70.

## Specifications

<b>Wattage</b>	11.8W - 13.7W
<b>Lumens</b>	850 lm - 1100 lm
<b>Voltage</b>	120/277V
<b>Dimmable</b>	TRIAC/ELV
<b>Lamp Type</b>	LED
<b>CRI</b>	93+
<b>Wet Location</b>	Listed

## Options



All Black



Black w/ White



All White



All Bronze

## Technical Details

**Optics:** Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Construction:** Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

**Trim:** Flexa™ Diecast 4" Round Reflector 2 peice trim for maxium color flexibility.

**Installation:** Twist-lock design for toolless trim installation, for use with E.L.L. trims only. Flexa™ 4" Reflecot Round Trims. Also compatible with E26, GU10, or GU24 base housings with PSA30, PSA31, or PSA35 socket adapters (sold separately). Available for use in IC and non-IC housings.

**Electrical:** Module connects to 120/277V power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

**LED Technology:** Extremely accurate Color Rendering Index of 93+. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

### Dimmability:

- Works with 120V Triac and ELV type dimmers.
- Dims down to 10%.
- For full list of dimmers, refere to the Dimmer Compatibility List.
- Industry leading dimming that dims smoothly with no hot spots or flickering.

**Listings:** UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2016-E.

**Warranty:** ELCO Products are built to last with a 5-year Limited Warranty.

## Product Numbers

Description	Lamp type	Lumens	Watts	Voltage	Dimming
850 LUMEN	LED	850 lm	11.8W	120/277V	TRIAC/ELV
1100 LUMEN	LED	1100 lm	13.7W	120/277V	TRIAC/ELV

## Product Number Builder Example:

Module	Lumen	CCT	-	Flexa Trim
<b>ELL</b> LED Module	<b>08</b> 850 lm <b>11</b> 1100 lm	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K <b>SD</b> Sunset	-	<b>ELL4643</b> Flexa Refl.
Baffle	Trim Ring			
<b>B</b> Black <b>BZ</b> Bronze <b>W</b> White	<b>B</b> Black <b>BZ</b> Bronze <b>W</b> White			