

E.L.L. Module with 4" Square Reflector FLEXA™ Trim



E.L.L. Module with 4" FLEXA™ Square Reflector Trim, FLEXA™ is 2 pieces for maximum design flexibility. FLEXA™ trims are available in round, square as a reflector or baffle.

Features

- Module with FLEXA™ twist and lock trim
- Smooth lens provides even lighting illumination
- ELL Module works in 4" & 6" housings with interchangeable trims.
- Twist-&-Lock System for easy trim installation.
- Excellent color rendering 93+ CRI.
- ENERGY STAR® Certified.
- Title 24 JA8 2016-E registered.
- Smooth and even dimming.
- Life span of 50,000 hours L70.

Specifications

Wattage	11.8W - 13.7W
Lumens	850 lm - 1100 lm
Voltage	120/277V
Dimmable	TRIAC/ELV
Lamp Type	LED
CRI	93+
Wet Location	Listed

Options



All Black



Black w/ White



All Bronze



Chrome w/ White



Haze w/ White



All White

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Trim: Flexa™ Diecast 4" Round Reflector 2 peice trim for maxium color flexibility.

Installation: Twist-lock design for toolless trim installation, for use with E.L.L. trims only. Flexa™ 4" Reflecot Round Trims. Also compatible with E26, GU10, or GU24 base housings with PSA30, PSA31, or PSA35 socket adapters (sold separately). Available for use in IC and non-IC housings.

Electrical: Module connects to 120/277V power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Extremely accurate Color Rendering Index of 93+. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

Dimmability:

- Works with 120V Triac and ELV type dimmers.
- Dims down to 10%.
- For full list of dimmers, refere to the Dimmer Compatibility List.
- Industry leading dimming that dims smoothly with no hot spots or flickering.

Listings: UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2016-E.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Numbers

Description	Lamp type	Lumens	Watts	Voltage	Dimming
850 LUMEN	LED	850 lm	11.8W	120/277V	TRIAC/ELV
1100 LUMEN	LED	1100 lm	13.7W	120/277V	TRIAC/ELV

Product Number Builder Example:

Module	Lumen	CCT	-	Flexa Trim
ELL LED Module	08 850 lm 11 1100 lm	27 2700K 30 3000K 35 3500K 40 4000K SD Sunset	-	ELL4641 Flexa Refl.

Reflector	Trim Ring
B Black BZ Bronze H Haze W White C Chrome	B Black BZ Bronze W White