

LED Clove II™ Track Fixture



Features

- Dimmable, solid die-cast aluminum, Cylinder fixture
- 90° vertical adjustment, 358° rotation
- Integrated driver
- ETL Listed
- 50,000 hours life-span
- 38° Beam Angle Standard. Optional Lenses: EP719C (15°) or EP720C (24°) available
- Use with ELCO 120V Single or Double Circuit Track.

Specifications

Wattage	14W
Lumens	1075 lm
Voltage	120V
Color Temp.	3000K
Dimmable	Triac
Lamp Type	LED
Beam Angle	38° Standard. Optional 15° & 24° available
CRI	90+

Options



White



Black

Technical Details

Construction: Full diecast construction for exceptional heat management and lasting quality. Powder coat architectural white and architectural black matte finishes.

Adjustability: Track head is adjustable 180° vertically with 358° rotation.

Optics: Lens provides smooth lumen output at standard 38°.

Installation: Effortlessly installed into H-Style track from ELCO or others. Compatible with Single and Double circuit track. Can be ordered as J-Style or L-Style.

LED Technology: Extremely accurate Color Rendering Index of 93+ CRI. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Instant On to Full Brightness technology. Chip on Board LED design results in a smooth lumen output with no LED pixelation

Dimmability: Triac and ELV dimmable down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.


Electrical:

- Driver is rated for 120V input
- High Efficiency driver with a power factor > 0.9

Listings: ETL Listed. RoHS Compliant

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
ET578L30W	LED	1075 lm	3000K	14W	120V	Triac	38° Standard. Optional 15° & 24° available	White
ET578L30B	LED	1075 lm	3000K	14W	120V	Triac	38° Standard. Optional 15° & 24° available	Black