

Pro	ject	na	me
	Juce	IIG	

Fixture type:

Date:

Lotus II™ LED Undercabinet Light



Features

- Mini linking connector included for row mounting
- Individually switch with pass-through power
- 2700K/3000K/3500K (CCT Switch)
- Linkable end-to-end On/Off switch
- Polycarbonate lens
- Dimmable driver included
- Hard wire or plug & play
- cUL listed
- 120V
- High CRI 90
- T24 JA8-2016 Compliant

Specifications


Wattage	6W - 18W
Lumens	360 lm - 1100 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K
Lamp Type	LED

Options



White

Dimensions



Product Numbers

Item	Description	Lamp type	Lumens	сст	Watts	Voltage	Finish
EU3T08W	8" Length	LED	360 lm	2700K, 3000K, 3500K	6W	120V	All White
EU3T12W	12" Length	LED	485 lm	2700K, 3000K, 3500K	8W	120V	All White
EU3T16W	16" Length	LED	610 lm	2700K, 3000K, 3500K	10W	120V	All White
EU3T24W	24" Length	LED	850 lm	2700K, 3000K, 3500K	14W	120V	All White
EU3T32W	32" Length	LED	1100 lm	2700K, 3000K, 3500K	18W	120V	All White

Product Number Builder Example: EU3T08W

Lotus 2™ Undercab. Bar	Length	Finish
EU3T		
	08 8 in	W All White
	12 12 in	
	16 16 in	
	24 24 in	
	32 32 in	



Dimmer Compatibility Chart for Lotus II™ Undercabinet Lights

EU3T Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturor	Product	Part Number	Dimmed Light Output Range
			10% - 100%
GE		_	10% - 100%
	Decora 4-Level Step Electro-Mechanical Incandescent Dimmer	6161-A	10% - 100%
	IllumaTech Slide Dimmer for 150-Watt Dimmable LED/CFL, 600-Watt Incandescent/Halogen	IPL06-10Z	10% - 100%
	IllumaTech 1000W Preset Incandescent Dimmer, Single Pole or 3-Way	IPIO-1LZ	10% - 100%
	IllumaTech 600W Preset Single-Pole & 3-Way Electro-Mechanical Incandescent Slide Dimmer	IPI06-1LZ	10% - 100%
Leviton	Decora SureSlide Universal LED Dimmer 60Hz Single Pole/3-Way	6674	10% - 100%
Leviton	Single Pole Rocker-Style Dimmer Switch 10464	6672-1LW	10% - 100%
GE	SureSlide 600W Decora Full Range Slide Dimmer	6633-POG	10% - 100%
		6681	10% - 100%
	Dimmer Lamp Socket 150W Incandescent Single-Pole	6151	10% - 100%
	SureSlide Incandescent Slide Dimmer	6633-I	10% - 100%
	Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer	MACL-153MR- WH	10% - 100%
	Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer	MACL-153P	10% - 100%
GE Single Pole Rocker Toggle-Style On/Of Decora 4-Level Ste IllumaTech Slide Di Incandescent/Halog IllumaTech 600W F Incandescent Slide Decora SureSlide L SureSlide 150W LE SureSlide 600W D Trimatron 600W S Push On/Off Switch Dimmer Lamp Sock SureSlide Incandes Maestro® Series 18 Maestro® Series 18 Skylark® 150W Sin Ariadni®/Toggler® DIVA® Series 150W Lutron Skylark Contour® 1 Lumea C•L Dimme Nova® Single Pole Skylark® Single Pole Dimmer Skylark Contour 30 Skylark 150-Watt S	Skylark® 150W Single Pole/3-Way Dimmer	SCL-153PR- WH	5% - 86%
	Ariadni®/Toggler® Series 150W Single Pole/3-Way Dimmer	TGCL-153P	10% - 100%
	DIVA® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	10% - 100%
Lutron	Skylark Contour® 150W Single Pole/3-Way Dimmer	CTCL-153P	10% - 100%
	Lumea C•L Dimmer - 150W LED/600W Incandescent/Halogen	LGCL-153P	10% - 100%
	Nova® Single Pole Incandescent/Halogen Slide-to-Off Dimmer	N-600	10% - 100%
		S-603PG	5% - 85%
	Skylark Contour 300W Electronic Low Voltage Single Pole/3-Way	CTELV-303P- WH	10% - 100%
	Skylark 150-Watt Single-Pole/3-Way Dimmer	SCL-153-LA	10% - 100%
	Ariadni®/Toggler® Series 150W Single Pole/3-Way Dimmer	TGCL-153P	5% - 86%

2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com

*NOTE: Refer to dimmer manufacturer's docum	nentation for installation instructions an	d circuit details		
Disclaimer: Minimum and maximum loads for LEDs and CFLs a does not imply certification by an independent laboratory or any	are given in number of lamps and may vary dependir y other standards certification. Refer to manufacture	g on the lamp being used. Testing ir specifications for more detailed in	conducted by ELCO Lighting is not a sub- nformation on product certifications and s	stitute for and tandards.
2042 E. Vernon Ave.	Vernon CA 90058 Tel 323.231.2600	Fax 323 231 3200	lcolighting.com	
ZOHZ E. VEITION AVE.	VOLUME OF SOURCE 1 CT 323.23 1.2000	1 an 323.231.3200 E	ioongnung.com	