

# Mini LED Step Light with Scoop

ELCO's Ibis Collection consists of diecast wet location mini LED Step Lights which are offered in 2W or 3W, 3000K or 4000K, 120V or 12V AC/DC in round or rectangle with an Angled Louver, Open Frame Lens or Scoop Faceplate in a sharp White, Black, Nickel or Copper powder coated finish.



## Features

- Single Piece Diecast aluminum faceplate.
- Powder Coated Faceplate.
- Vertical Mounting.
- Integrated LED board and driver.
- Diffused lens behind faceplate.
- Wet Location listed for indoor or outdoor use.
- Mounts in a standard single gang box.
- Life span of 50,000 hours L70.
- Input Volt: 12V or 120V. (12V units work with 12V AC or 12V DC supply)
- Rated: IP67.

## Specifications

|                     |               |
|---------------------|---------------|
| <b>Wattage</b>      | 2W            |
| <b>Voltage</b>      | 120V or 12V   |
| <b>Color Temp.</b>  | 3000K - 4000K |
| <b>Lamp Type</b>    | LED           |
| <b>CRI</b>          | 90+           |
| <b>Wet Location</b> | Listed        |

## Options



White



Black



Nickel



Copper



Bronze

## Technical Details

**Optics:** Frosted lens diffuses light and illuminates walkway.

**Construction:** Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Security screws for mounting faceplate to box included.

**Installation:** Easily installs into a standard single gang switch box.

### Electrical:


- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).
- 120V ELST98: Driver input of 120V 50/60Hz connects directly to line voltage power.
- 12V ELST94: Input of 12V requires an external transformer. (12V units work with 12V AC or 12V DC supply)

### LED Technology:

- 90+ CRI for extremely accurate color rendering.
- Lumen Maintenance of 50,000 hours L70 Life.
- LED Array.

**Listings:** cETLus listed for Wet Location.

## Dimensions



## Product Numbers

| Item      | Lamp type | CCT   | Watts | Voltage | Finish    |
|-----------|-----------|-------|-------|---------|-----------|
| ELST9430B | LED       | 3000K | 2W    | 12V     | All Black |
| ELST9440B | LED       | 4000K | 2W    | 12V     | All Black |
| ELST9430W | LED       | 3000K | 2W    | 12V     | All White |
| ELST9440W | LED       | 4000K | 2W    | 12V     | All White |
| ELST9430N | LED       | 3000K | 2W    | 12V     | Nickel    |

| Item              | Lamp type | CCT   | Watts | Voltage | Finish     |
|-------------------|-----------|-------|-------|---------|------------|
| <b>ELST9440N</b>  | LED       | 4000K | 2W    | 12V     | Nickel     |
| <b>ELST9430CP</b> | LED       | 3000K | 2W    | 12V     | Copper     |
| <b>ELST9440CP</b> | LED       | 4000K | 2W    | 12V     | Copper     |
| <b>ELST9430BZ</b> | LED       | 3000K | 2W    | 12V     | All Bronze |
| <b>ELST9440BZ</b> | LED       | 4000K | 2W    | 12V     | All Bronze |
| <b>ELST9830B</b>  | LED       | 3000K | 2W    | 120V    | All Black  |
| <b>ELST9840B</b>  | LED       | 4000K | 2W    | 120V    | All Black  |
| <b>ELST9830BZ</b> | LED       | 3000K | 2W    | 120V    | All Bronze |
| <b>ELST9840BZ</b> | LED       | 4000K | 2W    | 120V    | All Bronze |
| <b>ELST9830CP</b> | LED       | 3000K | 2W    | 120V    | Copper     |
| <b>ELST9840CP</b> | LED       | 4000K | 2W    | 120V    | Copper     |
| <b>ELST9830N</b>  | LED       | 3000K | 2W    | 120V    | Nickel     |
| <b>ELST9840N</b>  | LED       | 4000K | 2W    | 120V    | Nickel     |
| <b>ELST9830W</b>  | LED       | 3000K | 2W    | 120V    | All White  |
| <b>ELST9840W</b>  | LED       | 4000K | 2W    | 120V    | All White  |

# Product Number Builder

Example: **ELST9430B**

ELCO Mini LED Step Lights

ELST9

4 12V

8 120V

30 3000K

40 4000K

W All White

B All Black

N Nickel

CP Copper

BZ All Bronze

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • [elcolighting.com](http://elcolighting.com)  
© ELCO Lighting 2024. All rights reserved • Rev. 21 Dec 2022 • ELCO Lighting reserves the right to make specification and design changes without notice.


Page 2 of 3

# Photometric Report

## Mini LED Step Light with Scoop

### PHOTOMETRIC REPORT

Product #: ELST9840  
Wattage / Lumens: 2.1W / 8.3 lm  
Luminaire LPW: 3.9 lm/W



### CANDLE POWER SUMMARY

| Degree Vertical | 0° |
|-----------------|----|
| 0               | 3  |
| 5               | 3  |
| 15              | 3  |
| 25              | 2  |
| 35              | 2  |
| 45              | 1  |
| 55              | 1  |
| 65              | 0  |
| 75              | 0  |
| 85              | 0  |
| 90              | 0  |

### ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Center Beam Footcandles | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4'                       | 0.17                    | 6.0'          |
| 6'                       | 0.08                    | 9.0'          |
| 8'                       | 0.04                    | 12'           |
| 10'                      | 0.03                    | 15.1'         |

### ZONAL LUMEN SUMMARY

| Zone  | Lumens | %Luminaire |
|-------|--------|------------|
| 0-30° | 2.1    | 24.8       |
| 0-40° | 3.3    | 40.1       |
| 0-60° | 5.9    | 70.9       |
| 0-90° | 7.9    | 95         |