

# 5" Adjustable Pull Down LED Light Engine



## Features

- Frosted Lens provides smooth lumen distribution and eliminates LED pixelation.
- ENERGY STAR® Certified. California Title 24 (JA8-2016).
- Life Span of 50,000 Hours L70.
- Deep set LED reduces glare while providing area illumination.
- Compatible with ELCO Maple™ system frame.

## Specifications

<b>Wattage</b>	16W
<b>Lumens</b>	1100 lm
<b>Color Temp.</b>	3000K - 4000K
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	100°
<b>CRI</b>	93+
<b>Damp Location</b>	Listed

## Options



White



Bronze

## Technical Details

**Optics:** Polycarbonate diffuser with internal reflector create a uniform light distribution with minimal glare.

**Construction:** IC Rated for Direct Contact with Insulation in E5SQLFU11 housing. Diecast aluminum heatsink for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking. Adjustable pull down to 85° and rotation of 356°.

### Electrical:

- 1100 Lumen uses 16W.
- 120/277V input with E5SQLFU frame.

### LED Technology:

- Extremely accurate color rendering with 93+ CRI.
- Efficacy of 68 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing aluminum heat sink.

### Dimmability:

- Flicker-Free Dimming.
- E5SQLFU11 works with Triac/ELV type dimmers with 1100 Lumen Light Engine.
- Smoothly dims down to 10%. Dimming range may vary depending on dimmer model.
- For full list of dimmers refer to the Dimmer Compatibility List.

**Listings:** UL/cUL Listed for Damp Location.


UL Listed for Direct Contact with Insulation and Combustible Material.

ENERGY STAR® Certified. California Title 24 (JA8-2016).

Certified under ASTM-E283 for Air Tight Construction.

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Beam Angle	Finish
<b>E523L1130BZ</b>	LED	1100 lm	3000K	16W	100°	Bronze
<b>E523L1140BZ</b>	LED	1100 lm	4000K	16W	100°	Bronze
<b>E523L1130W</b>	LED	1100 lm	3000K	16W	100°	White
<b>E523L1140W</b>	LED	1100 lm	4000K	16W	100°	White


ELCO 5" Adjustable Pull-Down Light Engine	Color Temp.	Finish
<b>E523L11</b>	<b>30</b> 3000K <b>40</b> 4000K	<b>W</b> White <b>BZ</b> Bronze

## Compatible Products


For use with **5" Maple™** LED Square Light Engines



### 5" Maple™ IC Shallow Frame with Driver



IC Shallow Frame  
**Plaster Frame**



Optional:  
**Emergency Battery Backup**

CAT NO.	SPECIFICATIONS
E5SQLFU11	1100 lm
E5SQLFU20	2000 lm


CAT NO.	SPECIFICATIONS
E5SQLFU11EM1	1100 lm (Up to 750 lm Emergency Output)
E5SQLFU11EM2	1100 lm (Up to 1100 lm Emergency Output)
E5SQLFU20EM1	2000 lm (Up to 750 lm Emergency Output)
E5SQLFU20EM2	2000 lm (Up to 1100 lm Emergency Output)

### LED Light Engine

Multiplier: 4000K (x 1.08)

#### PHOTOMETRIC REPORT

Product #: E523L1130  
Wattage/Lumens: 15.9W/ 1140 Lm  
Luminaire LPW: 72 Lm/W



#### CANDLE POWER SUMMARY

Degrees Vertical	0°
0	499
5	496
15	469
25	420
35	352
45	270
55	186
65	102
75	32
85	5
90	0

#### ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	31.2	8.9'
6'	13.9	13.4'
8'	7.80	17.9'
10'	4.99	22.3'

#### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30°	374.59	32.80
0-40°	597.24	52.40
0-60°	982.50	86.20
0-90°	1140.31	100.00