

4" Shower Trim with Reflector and Clear Lens



Features

- Shower Trim with Reflector and Clear Lens.
- Lamp: 32W max CFL (PL-T), 40W MAX A19 or 50W MAX PAR20.
- O.D.: 4 3/4".

Technical Details


Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options



Product Numbers

Item	Finish
EL9111B	Black
EL9111SH	White Lexan
EL9111W	White

Product Number Builder

Example: EL9111B

4" Shower Trim with Reflector and Clear Lens

Finish

EL9111

- B

Black
- C

All Clear
- SH

White Lexan
- W

White
- G

Gold
- CP

Copper

Compatible Products

For use with 4" Trims for PAR Lamps



4" Line Voltage ICA Housings



4" Airtight IC Housing
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.




4" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
EL99RICA	Lamp: 50W MAX.



4" Housing
Remodel

CAT NO.	SPECIFICATIONS
EL99RA	Lamp: 50W MAX.



4" Airtight IC 2-Hour Fire Rated Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.



4" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC Housing with GU24 Base Socket
Remodel


CAT NO.	SPECIFICATIONS
EL99RICA-G24	Lamp: 18W MAX.

4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L