ELCO Lighting

Project Name:

Fixture Type:

Date:

1″ ROUND RECESSED OAK™ GIMBAL

Adjustable · Round · 1″ · 3 finishes



Small aperture 12V AC Downlight delivers over 600 lumens. More than a traditional 50W MR16 Halogen Lamp. Requires 12V AC Transformer (daisy chain up to 6). Dimmable ELV, MLV or 0-10V depending on transformer used.

FEATURES

- Requires 12V AC transformer. Dimmable ELV, MLV or 0-10V depending on transformer used.
- IC for use with direct contact to insulation
- Height allows for use in ceilings with under 3″ depth. Ceiling thickness can be reduced from fixture depth.
- Daisy chain up to 6 fixtures with E1LDRV60
- 38° Standard beam with optional 28° and 50°
- Remodel requires no frame. New construction E1LF2 frame available.
- UL Damp Location Rated
- UL Listed, Meets California Title 24 JA8-2025-E standards.
- Life Span 50,000 Hours L70

DIMENSIONS



SPECIFICATIONS

Wattage	6.1W
Lumens	625 · 650 · 675 · 700 lm
Voltage	12V AC
Color temp.	2700K · 3000K · 3500K · 4000K
Dimming	Dimmable
Lamp type	LED
Beam angle	38° · 28° · 50°
Aperture	1"
Shape	Round

FINISHES


White


Bronze


Black

Item page
elcolighting.com/items/1-round-recessed-adjustable-oak-gimbal
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

Low Voltage Oak™

⬇ Dimmer compatibility list
elcolighting.com · Dimmer - Oak System (ELV)

© ELCO Lighting 2026. All rights reserved • Rev. 27 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **1" Round Recessed Oak™ Gimbal** item number (Select one) Example: **E1L32F27W** Your item number:

ITEM	SHAPE	BEAM ANGLE	CCT	FINISH
E1L	**32** Round	**F** 38° **NF** 28° **WF** 50°	**27** 2700K **30** 3000K **35** 3500K **40** 4000K	**W** White **BZ** Bronze **B** Black

TECHNICAL DETAILS

Optics: PC Lens for even lumen distribution. Standard 38° lens. Optional 28° (EP713C) and 50° (EP715C) available.

Adjustability: 360° rotation with 30° gimbal adjustability. Gimbal can be locked into place by tightening locking screw.

Construction: Diecast construction for lasting quality and greater heat dissipation. High quality powder coat finish prevents rust and paint cracking.

Installation: Requires 12V AC transformer. Can be installed on E1LF2 new construction frame. Remodel requires no frame. Hole cutout size: 2 3/8" (60 mm). Height allows for use in ceilings with under 3" depth. Ceiling thickness can be reduced from fixture depth.

LED Technology: 93+ CRI color rendering. Efficacy of up to 110 lumens per watt. Lumen Maintenance of 50,000 hours L70 based on LM80. Thermal management by utilizing diecast aluminum body as heat sink.

Electrical: Requires 12V AC transformer. Can be daisy chained up to 6 fixtures with E1LDRV60 or can be wired 1 fixture per transformer.

Delivered Lumens: E1L32F27 625 lm/2700K **E1L32F30** 650 lm/3000K **E1L32F35** 675 lm/3500K **E1L32F40** 700 lm/4000K

Dimming: Dims with MLV dimmers when powered by dimmable magnetic 12V AC transformer. Works with ELV dimmers when powered by dimmable electronic 12V AC transformer. Dims with 0-10V systems with 0-10V dimmable 12V AC transformer. Check transformer and dimmer compatibility before installation.

Listings: UL Listed (US and Canada). UL Listed for DAMP Location. UL Listed for direct contact with insulation. Meets California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 27 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.