ELCO Lighting

Project Name:

Fixture Type:

Date:

2″ KOTO SYLO™ DIRECT MOUNT

Direct Mount · 2″ · 3 finishes

Works with Koto™ Standard LED Module



FEATURES

- Modern Die-Cast aluminum fixture for easy maintenance and upgrades
- Includes Standard 38° lens, with 25° and 60° lenses. Optional: 18° & 90° lenses available.
- Directly mounts into ceiling (Up to 1.5″ ceiling thickness)
- Optional mounting plate (E1LF1)
- Sunset option dims from 3000K to 1800K
- Tunable White option dims from 1800K to 4000K
- Human Centric option dims from 4000K to 2200K
- Title 24 JA8-2025-E & Energy Star Compliant
- Life span of 50,000 hours L70
- **120V Triac/ELV** with standard module options (-03, -07, -08, -09, -10, -11, -13 series)
  120/277V, 0-10V/Triac/ELV with DX module (-10DX series)

DIMENSIONS



SPECIFICATIONS

Wattage	10.5 · 12.5 · 5 · 11.5 · 11.8 W
Lumens	350 · 750 · 825 · 880 · 950 · 1000 · 1150 · 1350 lm
Voltage	120V · 120-277V
Color temp.	2400K · 2700K · 3000K · 3500K · 4000K · Sunset · Human Centric · 2700K-5000K · 1800K-4000K · Tunable White
Dimming	Triac/ELV · DALI 2 Controlled · 0-10V/Triac/ELV
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 10° · 90°
CRI	95+
Aperture	2"
Mounting style	Direct Mount
Module	350 · 750 · 825 · 850 · 950 · 1000 · 1150 · 1350 · 880 lm

FINISHES



White



Black



Silver

Item page
elcolighting.com/items/2-koto-sylo-direct-mount
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ Koto Sylo™ Direct Mount

↓ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **2" Koto Sylo™ Direct Mount** item number (Select one) Example: **E25DW-0727** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	CCT	BEAM ANGLE
E25	**D** Direct Mount	**W** White **B** Black **S** Silver	**-03** 350 lm (5W)[1, 2] **-07** 750 lm (10.5W)[1] **-08** 825 lm (10.5W)[1, 3] **-08AL** 850 lm (11.5W)[4] **-09** 950 lm (10.5W)[1] **-10** 1000 lm (12.5W)[1, 3] **-11** 1150 lm (12.5W)[1] **-13** 1350 lm (12.5W)[1] **-10DX** 1000 lm (11.8W)[5] **-08A** 880 lm (11.5W)[4]	**24** 2400K **27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[6, 7] **HC** Human Centric[1, 8, 9] **CT5** 2700K-5000K[1, 10] **4T** 1800K-4000K[11] Tunable White	38° **-S** 18° **-N** 25° **-W** 60° **-T** 10°[1, 12] **-E** 90°[13]

[1] Available as 120V, Triac/ELV only [2] Available with 2400K, 2700K and 3000K Color Temperature Only [3] Available with CT5 color temperature only [4] DALI 2, 120/277V [5] 120/277V, 0-10V/Triac/ELV [6] Available in -09 & -11 lumen outputs only [7] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [8] Available with 1150 lumen (-11) outputs only [9] Human Centric, Dim to Warm technology, automatically transitions from 4000K to 2200K when dimmed [10] Available with -08 and -10 lumen outputs only [11] Available with -08A (880 lm) output only, Dali 2 dimmable and Tunable White [12] Available with 350 and 750 lumen, 2700K and 3000K options only [13] 90° Frosted Reflector

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-lock design for toolless trim installation, for use with Koto Sylo™ products only. Optional E1LF1 Mounting Plate.

Electrical: 120V or 120-277V Input Module. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens:

0327 2700K/442.8 lm/5W **0330** 3000K/461.2 lm/5W

0727 2700K/770 lm/10.5W **0730** 3000K/800 lm/10.5W **0735** 3500K/830 lm/10.5W **0740** 4000K/860 lm/10.5W

08CT5 2700K/728.5 lm/10.5W **08CT5** 3000K/886 lm/10.5W **08CT5** 3500K/902 lm/10.5W
08CT5 4000K/920 lm/10.5W **08CT5** 5000K/931 lm/10.5W

0927 2700K/912 lm/10.5W **0930** 3000K/950 lm/10.5W **0935** 3500K/990 lm/10.5W **0940** 4000K/1030 lm/10.5W **09SD** Sunset/940 lm/10.5W

10CT5 2700K/908 lm/12.5W **10CT5** 3000K/1012 lm/12.5W **10CT5** 3500K/1038 lm/12.5W
10CT5 4000K/1040 lm/12.5W **10CT5** 5000K/1032 lm/12.5W

1124 2400K/730 lm/12.5W **1127** 2700K/1068 lm/12.5W **1130** 3000K/1112 lm/12.5 **1135** 3500K/1156 lm/12.5W **1140** 4000K/1202 lm/12.5W **11SD** Sunset/1050 lm/12.5W **11HC** Human Centric/1050 lm/12.5W

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.
Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute. HUMAN CENTRIC start at 4000K and go as low as 2200K when dimmed.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 5%. For full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.