ELCO Lighting

Project Name:

Fixture Type:

Date:

2″ KOTO SYLO™ PENDANT

Pendant · 2″ · 3 finishes

Works with Koto™ Standard LED Module

FEATURES

- Modern Die-Cast aluminum fixture for easy maintenance and upgrades
- Available with 120″ Field Cuttable Cable or Stems (12", 24", 36", 48", 60", 72" and 84")
- Includes Standard 38° lens, with 25° and 60° lenses. Optional: 18° & 90° lenses available.
- Fits 3 ½″ and 4″ Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- Tunable White option dims from 1800K to 4000K
- Human Centric option dims from 4000K to 2200K
- Energy Star Certified. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- **120V Triac/ELV** with standard module options (-03, -07, -08, -09, -10, -11, -13 series)
  120/277V, 0-10V/Triac/ELV with DX module (-10DX series)

DIMENSIONS



Dimensions with Stem



Dimensions with Stem

SPECIFICATIONS

Wattage	10.5 · 12.5 · 5 · 11.8 · 11.5 W
Lumens	350 · 750 · 825 · 880 · 950 · 1000 · 1150 · 1350 lm
Voltage	120V · 120-277V
Color temp.	2400K · 2700K · 3000K · 3500K · 4000K · Sunset · Human Centric · 2700K-5000K · 1800K-4000K · Tunable White
Dimming	Triac/ELV · 0-10V/Triac/ELV · DALI 2 Controlled
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 10° · 90°
CRI	95+
Aperture	2"
Mounting style	Pendant
Module	350 · 750 · 825 · 850 · 950 · 1000 · 1150 · 1350 · 880 lm
Length	120" Cable Mount · 12" Stem · 24" Stem · 36" Stem · 48" Stem · 60" Stem · 72" Stem · 84" Stem

FINISHES

White


Black


Silver

Item page
elcolighting.com/items/2-koto-sylo-pendant
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ Koto Sylo™ Pendant

↓ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 11 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **2" Koto Sylo™ Pendant** item number (Select one) Example: **E25PW-0727** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	CCT	BEAM ANGLE	LENGTH
E25	**P** Pendant	**W** White **B** Black **S** Silver	**-03** 350 lm (5W)[1, 2] **-07** 750 lm (10.5W)[1] **-08** 825 lm (10.5W)[1, 3] **-08AL** 850 lm (11.5W)[4] **-09** 950 lm (10.5W)[1] **-10** 1000 lm (12.5W)[1, 3] **-11** 1150 lm (12.5W)[1] **-10DX** 1000 lm (11.8W)[5] **-13** 1350 lm (12.5W)[1] **-08A** 880 lm (11.5W)[4]	**24** 2400K **27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[6, 7] **HC** Human Centric[8, 9] **CT5** 2700K-5000K[1, 10] **4T** 1800K-4000K[11] Tunable White	38° **-S** 18° **-N** 25° **-W** 60° **-T** 10°[1, 12] **-E** 90°[13]	120" Cable Mount[14] **-12** 12" Stem[15] **-24** 24" Stem[15] **-36** 36" Stem[15] **-48** 48" Stem[15] **-60** 60" Stem[15] **-72** 72" Stem[15] **-84** 84" Stem[15]

[1] Available as 120V, Triac/ELV only [2] Available with 2400K, 2700K and 3000K Color Temperature Only [3] Available with CT5 color temperature only [4] DALI 2, 120/277V [5] 120/277V, 0-10V/Triac/ELV [6] Available in -09 & -11 lumen outputs only [7] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [8] Available with 1150 lumen (-11) outputs only [9] Human Centric, Dim to Warm technology, automatically transitions from 4000K to 2200K when dimmed [10] Available with -08 and -10 lumen outputs only [11] Available with -AL option only, Dali 2 dimmable Tunable White [12] Available with 350 and 750 lumen, 2700K and 3000K options only [13] 90° Frosted Reflector [14] 120 inch field cuttable cable [15] Stem is not field cuttable

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless trim installation, for use with Koto Sylo™ products only.

Electrical: 120V or 120-277V Input Module. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Delivered Lumens:

0327 2700K/442.8 lm/5W **0330** 3000K/461.2 lm/5W

0727 2700K/770 lm/10.5W **0730** 3000K/800 lm/10.5W **0735** 3500K/830 lm/10.5W **0740** 4000K/860 lm/10.5W

08CT5 2700K/728.5 lm/10.5W **08CT5** 3000K/886 lm/10.5W **08CT5** 3500K/902 lm/10.5W **08CT5** 4000K/920 lm/10.5W **08CT5** 5000K/931 lm/10.5W

0927 2700K/912 lm/10.5W **0930** 3000K/950 lm/10.5W **0935** 3500K/990 lm/10.5W **0940** 4000K/1030 lm/10.5W **09SD** Sunset/940 lm/10.5W

10CT5 2700K/908 lm/12.5W **10CT5** 3000K/1012 lm/12.5W **10CT5** 3500K/1038 lm/12.5W **10CT5** 4000K/1040 lm/12.5W **10CT5** 5000K/1032 lm/12.5W

10DX27 2700K/979 lm/11.8W **10DX30** 3000K/1020 lm/11.8W **10DX35** 3500K/1060 lm/11.8W **10DX40** 4000K/1103 lm/11.8W **10DXSD** Sunset/1000 lm/11.8W
1124 2400K/730 lm/12.5W **1127** 2700K/1068 lm/12.5W **1130** 3000K/1112 lm/12.5 **1135** 3500K/1156 lm/12.5W **1140** 4000K/1202 lm/12.5W **11SD** Sunset/1050 lm/12.5W **11HC** Human Centric/1050 lm/12.5W

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 11 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.