ELCO Lighting

Project Name:

Fixture Type:

Date:

2″ SYLO™ MONOPOINT WITH KOTO™ FOCUS MODULE

Monopoint · 2″ · 3 finishes

Adjustable Focus: 18° to 50° with a simple twist of the snoot



FEATURES

- Modern Die-Cast aluminum fixture for easy maintenance and upgrades
- Standard Fixtures or Fixtures with Stems (12", 24", 36", 48", and 60") available
- Fits 3 ½″ and 4″ Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- 90° tilt, 358° rotation
- Energy Star Certified. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- Integrated 120V Dimmable Driver Triac/ELV
- 95+ CRI color rendering
- Covered by U.S. PATENTS and Patents Pending

DIMENSIONS



SPECIFICATIONS

Wattage	10.5W
Lumens	720 · 770 · 800 · 830 · 860 lm
Voltage	120V
Color temp.	2700K · 3000K · 3500K · 4000K · Sunset
Dimming	Triac/ELV
Lamp type	LED
Beam angle	18° - 50° · Adjustable Beam 18° - 50°
CRI	95+
Aperture	2"
Mounting style	Monopoint
Module	770 lm - 860 lm (10.5W)
Length	Standard · 12" Stem · 24" Stem · 36" Stem · 48" Stem · 60" Stem

FINISHES


White


Black


Silver

Item page
elcolighting.com/items/2-sylo-monopoint-koto-focus-module
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ Koto Sylo™ Monopoint

↓ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **2" Sylo™ Monopoint with Koto™ Focus Module** item number (Select one) Example: **E25MW-0727-FC** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	CCT	BEAM ANGLE	LENGTH
E25	**M** Monopoint	**W** White **B** Black **S** Silver	**-07** 770 lm - 860 lm (10.5W)	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset	**-FC** 18° - 50° Adjustable Beam 18° - 50°	Standard **-12** 12" Stem[1] **-24** 24" Stem[1] **-36** 36" Stem[1] **-48** 48" Stem[1] **-60** 60" Stem[1]

[1] Stem is not field cuttable

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-lock design for toolless trim installation, for use with Koto Sylo™ only. Adjustable Focus: 18° to 50° with a simple twist of the lens.

Electrical: 120V Input Module. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens:

ELK0727 770 lm/2700K **ELK0730** 800 lm/3000K **ELK0735** 830 lm/3500K **ELK0740** 860 lm/4000K

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing an integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For a full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. UL Listed (US and Canada) for Wet Location with Wet location trims. RoHS Compliant. Meets California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.