ELCO Lighting

Project Name:

Fixture Type:

Date:

24V DC 4″ DEDICATED LED IC AIRTIGHT NEW CONSTRUCTION R60 AND CHICAGO PLENUM HOUSING



Housing

24V DC 4″ R60 & Chicago Plenum New Construction LED Housing. Compatible with 24V DC Koto Module.

ITEM NUMBER **E24V490AJICA**

FEATURES

- Only for use with 24V DC Koto Module
- Dedicated LED New Construction IC Airtight R-60 Foam Insulation Housing
- Simple installation with 24V Wire
- Meets Title 24 requirements. ENERGY STAR® Certified.
- Trims and module sold separately
- Suitable for Chicago Plenum construction

DIMENSIONS



SPECIFICATIONS

Wattage	14W
Voltage	24V DC
Lamp type	LED

Item page
elcolighting.com/items/24v-dc-4-dedicated-led-ic-airtight-new-construction-r60-and-chicago-plenum-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ 24V DC Koto™

TECHNICAL DETAILS

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x6 joists or taller joists are used. High strength hanger bars can easily be nailed to joists. Maximum hole cutout is 4 1/4". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts slots.

Hanger Bars: Pre-installed hanger bars with True Nail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

© ELCO Lighting 2026. All rights reserved • Rev. 24 Jun 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

Electrical: Input Voltage: 24V DC.

Listings:

- UL Listed (US and Canada) for Damp Location.
- UL Listed (US and Canada) for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2025-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants this product will be free from defects in materials and workmanship for a period of 5 years.

© ELCO Lighting 2026. All rights reserved • Rev. 24 Jun 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.