ELCO Lighting

Project Name:

Fixture Type:

Date:

24V DC 6″ NEW CONSTRUCTION DEDICATED IC AIRTIGHT HOUSING

Housing · 6″



24V DC 6″ new construction dedicated LED housing. Compatible with 24V DC Koto Module

ITEM NUMBER **E24V770ICA**

FEATURES

- Only for use with 24V DC Koto Module
- IC Airtight for direct contact with insulation.
- Simple installation with 24V Wire
- Meets Title 24 Requirements. ENERGY STAR® Certified.
- Trims and module sold separately.

DIMENSIONS



SPECIFICATIONS

Wattage	24W MAX
Voltage	24V DC
Aperture	6"

Item page
elcolighting.com/items/24v-dc-6-new-construction-dedicated-ic-airtight-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

6″ 24V DC Koto™

TECHNICAL DETAILS

Construction:

- Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x8 joists or taller joists are used. High-strength hanger bars can easily be nailed to joists. Maximum hole cutout is 6 1/4". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts, four 3/4" knockouts. Pry-out knockout slots. 4 Romex pryouts with strain relief.

Hanger Bars: Pre-installed hanger bars with TrueNail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

Electrical:

- Input Voltage: 24V DC.
- Inherently protected.

Lamp: Designed for use with ELCO 24V DC Koto Module and trims.

Listings:

- UL Listed (US and Canada) for Damp Location.
- UL Listed (US and Canada) for Wet Location with select trims.
- UL Listed (US and Canada) for Feed Through.
- UL Listed (US and Canada) for Direct Contact with Insulation and

© ELCO Lighting 2026. All rights reserved • Rev. 24 Jun 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

Combustible Material.

- Airtight per ASTM E-283.
- Install a JA8-2025-E lamp for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

© ELCO Lighting 2026. All rights reserved • Rev. 24 Jun 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.