ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ 0-10V REMODEL DEDICATED LED IC AIRTIGHT HOUSING

Housing · 3″




3" Remodel LED Housing compatible with 0-10V LED Koto™ Module.

ITEM NUMBER **EL390RICDXA**

FEATURES

•Wired for 0-10V Dimming
•120/277V Input
•IC Airtight for direct contact with insulation.
•UL Listed (US and Canada) for direct contact with Insulation

DIMENSIONS



SPECIFICATIONS

Voltage	120-277V
Dimming	0-10V/Triac/ELV
Aperture	3"

Item page
elcolighting.com/items/3-0-10v-remodel-dedicated-led-ic-airtight-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

3″ DX Koto™

TECHNICAL DETAILS

Construction:

- IC rated for direct contact with insulation, for use in IC or Non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x6 joists or taller joists are used. Maximum hole cutout is 3 5/8". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Electrical: Input Voltage: 120277V

Lamp: Designed for use with GU10 MR16 LED lamps.

Dimmability: Dimmability based on lamp.

Listings:

- UL Listed (US and Canada) for Damp Location.
- UL Listed (US and Canada) for Wet Location with select trims.
- UL Listed (US and Canada) for Feed Through.
- UL Listed (US and Canada) for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2025-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.