ELCO Lighting


Project Name:

Fixture Type:

Date:

# 3″ 0-10V SHALLOW MAX. ADJUSTABILITY IC AIRTIGHT NEW CONSTRUCTION HOUSING

**Housing · 3″**




3" Shallow New Construction LED Housing compatible with 0-10V LED Koto™ Module.

## FEATURES

- Wired for 0-10V Dimming, 120/277V Input
- Integrated collar allows for use with ⅝" thick to 1 ½" thick ceilings
- Double Wall IC Airtight for direct contact with Insulation
- Meets restricted air flow requirements (per ASTM E-283)
- UL Listed for direct contact with Insulation, UL Listed for Damp Locations, UL Listed for Wet Location with Wet Location Rated Inserts, UL Listed for Feed Through, CA Title 24 Compliant

## DIMENSIONS




EL362ICDXA

## SPECIFICATIONS

| | |
|---|---|
| Voltage | 120-277V |
| Dimming | 0-10V/Triac/ELV |
| Aperture | 3" |

## ITEM NUMBERS

| ITEM NUMBER | VOLTAGE | DIMMING |
|---|---|---|
| **EL362ICDXA** | 120-277V | 0-10V/Triac/ELV |

**Item page**
elcolighting.com/items/3-0-10v-shallow-max-adjustability-ic-airtight-new-construction-housing
Every item number, IES files, downloads and the latest revision.

## PART OF THESE FAMILIES

3″ DX Koto™

## TECHNICAL DETAILS

**Construction:**

- IC rated for direct contact with insulation, for use in IC or Non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

**Installation:** Designed for ceiling plenums where 2x6 joists or taller joists are used. High strength swivel hanger bars can easily be nailed to joists. Maximum hole cutout is 3 5/8". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts, four 3/4" knockouts with pry-out knockout slots. 4 Romex pryouts with strain relief.

**Hanger Bars:** Pre-installed swivel hanger bars with TrueNail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

**Electrical:** Input Voltage: 120/277V.

**Emergency Backup:** The fixture becomes 120V only.

**Dimmability:** Dimmability based on lamp.


© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

**Lamp:** Designed for use with ELCO 3" Koto Twist-On Trims and DX Koto™ LED module

**Listings:** UL Listed for direct contact with Insulation, UL Listed for Damp Locations, UL Listed for Wet Location with Wet Location Rated Inserts, UL Listed for Feed Through, CA Title 24 Compliant. Airtight per ASTM E-283.

**Warranty:** ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.


© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.