ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ KOTO SYLO™ TRACK HEAD

Track Head · 3″ · 3 finishes



FEATURES

- Modern Track Head Die-Cast aluminum fixture for easy maintenance and upgrades
- Standard Fixtures or Fixtures with Stems (12″) available
- Includes Standard 38° lens, with 25° and 60° lenses. Optional: 18° & 90° lenses available.
- Works with Single and Two Circuit Track
- Sunset option dims from 3000K to 1800K
- Human Centric option dims from 4000K to 2200K
- 90° tilt, 358° rotation
- ENERGY STAR compliant. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- Standard H style, J & L Styles available

DIMENSIONS



Dimensions with Stem



Dimensions with Stem

SPECIFICATIONS

Wattage	10.5 · 12.5 · 5 · 14.7 · 18.9 W
Lumens	350 · 750 · 825 · 950 · 1000 · 1150 · 1500 · 1800 lm
Voltage	120V
Color temp.	2400K · 2700K · 3000K · 3500K · 4000K · Sunset · Human Centric · 2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 10° · 90°
CRI	95+
Aperture	3"
Mounting style	Track Head
Module	350 · 750 · 950 · 1150 · 1350 · 1500 · 1800 · 825 · 1000 lm
Length	Standard · 12" Stem

FINISHES



White



Black



Silver

Item page
elcolighting.com/items/3-koto-sylo-track-head
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ and 3″ Koto Sylo™ Track Head

⬇ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **3" Koto Sylo™ Track Head** item number (Select one) Example: **E36TW-0727** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	CCT	BEAM ANGLE	LENGTH
E36	**T** Track Head	**W** White **B** Black **S** Silver	**-03** 350 lm (5W)[1] **-07** 750 lm (10.5W) **-09** 950 lm (10.5W) **-11** 1150 lm (12.5W) **-13** 1350 lm (12.5W) **-15** 1500 lm (14.7W) **-18** 1800 lm (18.9W) **-08** 825 lm (10.5W)[2] **-10** 1000 lm (12.5W)[2]	**24** 2400K **27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[3, 4] **HC** Human Centric[5, 6] **CT5** 2700K-5000K[7]	38° **-S** 18° **-N** 25° **-W** 60° **-T** 10°[8, 9] **-E** 90°[10]	Standard **-12** 12" Stem[11]

[1] Available with 2400K, 2700K and 3000K Color Temperature Only [2] Available with CT5 color temperature only [3] Available with -09, -11, -13 and -15 lumen outputs only [4] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [5] Available with 1150 lumen (-11) outputs only [6] Human Centric, Dim to Warm technology, automatically transitions from 4000K to 2200K when dimmed [7] Available with -08 and -10 lumen outputs only [8] Available as 120V, Triac/ELV only [9] Available with 350 and 750 lumen, 2700K and 3000K options only [10] 90° Frosted Reflector [11] Stem is not field cuttable

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless module installation.

Electrical: Module connects to 120V power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute. HUMAN CENTRIC start at 4000K and go as low as 2200K when dimmed.

Delivered Lumens:

0327 2700K/442.8 lm/5W **0330** 3000K/461.2 lm/5W

0727 2700K/770 lm/10.5W **0730** 3000K/800 lm/10.5W **0735** 3500K/830 lm/10.5W **0740** 4000K/860 lm/10.5W

08CT5 2700K/728.5 lm/10.5W **08CT5** 3000K/886 lm/10.5W **08CT5** 3500K/902 lm/10.5W
08CT5 4000K/920 lm/10.5W **08CT5** 5000K/931 lm/10.5W

0927 2700K/912 lm/10.5W **0930** 3000K/950 lm/10.5W **0935** 3500K/990 lm/10.5W **0940** 4000K/1030 lm/10.5W **09SD** Sunset/940 lm/10.5W

10CT5 2700K/908 lm/12.5W **10CT5** 3000K/1012 lm/12.5W **10CT5** 3500K/1038 lm/12.5W
10CT5 4000K/1040 lm/12.5W **10CT5** 5000K/1032 lm/12.5W

1124 2400K/730 lm/12.5W **1127** 2700K/1068 lm/12.5W **1130** 3000K/1112 lm/12.5 **1135** 3500K/1156 lm/12.5W **1140** 4000K/1202 lm/12.5W **11SD** Sunset/1050 lm/12.5W **11HC** Human Centric/1050 lm/12.5W

1327 2700K/1260 lm/12.5W **1330** 3000K/1312 lm/12.5W **1335** 3500K/1365 lm/12.5W **1340** 4000K/1420 lm/12.5W

1527 2700K/1439 lm/14.7W **1530** 3000K/1501 lm/14.7W **1535** 3500K/1565 lm/14.7W **1540** 4000K/1627 lm/14.7W

Dimmability: For full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: RoHS Compliant. Meets ENERGY STAR and California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.