ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ LOW VOLTAGE KOTO SYLO™ MONOPOINT

Monopoint · 3″ · 3 finishes

Works with 12V AC and 24V DC Koto™ LED Module



FEATURES

- Modern Monopoint Die-Cast aluminum fixture for easy maintenance and upgrades
- Available with 120″ Field Cuttable Cable or Stems (12", 24", 36", 48", 60", 72" and 84")
- Includes Standard 38° lens, with 25° and 60° lenses. Optional: 18° & 90° lenses available.
- Low Voltage fixtures (24V DC and 12V AC options)
- Fits 3 ½″ and 4″ Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- Energy Star Compliant. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- **Sunset** with 12V AC LED Module only (12A)

DIMENSIONS





SPECIFICATIONS

Wattage	9 · 10 W
Lumens	800 lm
Voltage	12V AC · 24V DC
Color temp.	2700K · 3000K · Sunset
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 10° · 90° · 25°, 38°, 60°
CRI	95+
Aperture	3"
Mounting style	Monopoint
Module	800 lm (9W-10W)
Length	Standard · 12" Stem · 24" Stem · 36" Stem · 48" Stem · 60" Stem · 72" Stem · 84" Stem

FINISHES


White


Black


Silver

Item page
elcolighting.com/items/3-low-voltage-koto-sylo-monopoint
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

3″ Koto Sylo™ Monopoint

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **3" Low Voltage Koto Sylo™ Monopoint** item number (Select one) Example: **E36MW-0812A27** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	VOLTAGE	CCT	BEAM ANGLE	LENGTH
E36	**M** Monopoint	**W** White **B** Black **S** Silver	**-08** 800 lm (9W-10W)	**12A** 12V AC **24D** 24V DC	**27** 2700K **30** 3000K **SD** Sunset[1, 2]	38° **-S** 18° **-N** 25° **-W** 60° **-T** 10° **-E** 90°[3]	Standard **-12** 12" Stem[4] **-24** 24" Stem[4] **-36** 36" Stem[4] **-48** 48" Stem[4] **-60** 60" Stem[4] **-72** 72" Stem[4] **-84** 84" Stem[4]

[1] Available in 12A (12V AC) voltage only [2] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [3] 90° Frosted Reflector [4] Stem is not field cuttable

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-lock design for toolless trim installation, for use with Koto Sylo™ products only.

Electrical: High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatibility List.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.