ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ ROUND ADJUSTABLE EYEBALL DOWNLIGHT WITH 5-CCT SWITCH

Canless LED · Round


The innovative 3″ Floating Eyeball offers 360˚ rotation and a 90˚ tilt range for added versatility



FEATURES

- 8W / 600 lm
- IC Rated for direct contact to insulation
- CRI 90+
- CA Title 24 compliant
- 120V, Dimmable Triac/ELV
- For EM Backup use KEM-ERT

DIMENSIONS



SPECIFICATIONS

Wattage	8W
Lumens	600 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	34°
CRI	90+
Shape	Round

FINISHES

White

Item page
elcolighting.com/items/3-round-adjustable-eyeball-downlight-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

3″ Elm™

⬇ Dimmer compatibility list
elcolighting.com · Elm Dimmer Compatibility

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **3" Round Adjustable Eyeball Downlight with 5-CCT Switch** item number (Select one) Example: **ERT317CT5W** Your item number:

ITEM	CCT	FINISH
ERT317		
	CT5 2700K-5000K	**W** White

TECHNICAL DETAILS

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: Aluminum die-cast trim with durable powdercoat finish. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for proper trim installation.

Electrical: Included driver connects directly to 120V power supply. Standard input wattage is 8W, 75 lumens per watt. Open Driver box to switch color temperatures

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatability List.

Listings: ETL Listed for DAMP Locations. IC-Rated for direct contact with insulation. Air Tight certified in accordance with ASTM E283-2004. California Title 24 Compliant (JA8-2025-E)

Warranty: 5-year limited warranty.



360˚ Rotation



90˚ Tilt Range

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.