ELCO Lighting

Project Name:

Fixture Type:

Date:

3" ROUND LED REFLECTOR INSERT

Light Engine · Round · 3″ · 2 finishes



ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 90+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications.

FEATURES

- Fits ELCO 3″ Dedicated LED Recessed Housings for New Construction and Remodel.
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation.
- Deep set LED trim reduces glare while providing area illumination.
- Diecast construction provides lasting durability.
- ENERGY STAR® compliant
- Title 24 JA8-2025-E Compliant
- Life Span of 50,000 hours L70.

DIMENSIONS



SPECIFICATIONS

Wattage	9 · 11 W
Lumens	710 · 1040 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	90°
CRI	90+
Aperture	3"
Shape	Round

FINISHES


White


Bronze

Item page
elcolighting.com/items/3-round-led-reflector-insert
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

3″ LED Housings and Inserts

↓ Dimmer compatibility list

elcolighting.com · 3" LED Inserts Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **3" Round LED Reflector Insert** item number (Select one) Example: **EL312CT5W** Your item number:

ITEM	LUMENS	CCT	FINISH
EL3	**12** 710 lm **17** 1040 lm (11W) 1040 lm	**CT5** 2700K-5000K	**W** White **BZ** Bronze

TECHNICAL DETAILS

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED Array technology.

Construction: For use in IC and non-IC housings. Diecast construction for lasting quality and greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Quick connect for use with ELCO housings EL390ICA, EL390RICA, EL39FICA**.**

Electrical: Driver connects to120V power supply. High Efficiency driver with a power factor > 0.9.

LED Technology:

•90+ CRI color rendering.
•Lumen Maintenance of 50,000 hours L70 life based on LM80 standardized test results.
•Thermal management by utilizing integral heat sink.
•Instant On to Full Brightness.
•No LED pixelation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

Listings:

• UL Listed (US and Canada) 1598 Luminaire
• UL Listed (US and Canada) for Wet Location
• RoHS Compliant
• ENERGY STAR® compliant
• Title 24 JA8-2025-E Compliant

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.