ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ SHALLOW MAX. ADJUSTABILITY IC AIRTIGHT NEW CONSTRUCTION HOUSING

Housing · 3″



FEATURES

- IC Airtight for direct contact with insulation
- 120V Quick Connect for easy module installation
- Integrated collar allows for use with ½" thick to 1 ½" thick ceilings
- Limited 5 year warranty

DIMENSIONS



EL362ICA

SPECIFICATIONS

Voltage	120V
Dimming	Triac/ELV
Aperture	3"

ITEM NUMBERS

ITEM NUMBER	VOLTAGE	DIMMING
EL362ICA	120V	Triac/ELV

Item page
elcolighting.com/items/3-shallow-max-adjustability-ic-airtight-new-construction-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

3″ LED Housings and Inserts · 3″ Standard Koto™

TECHNICAL DETAILS

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x4 joists or taller joists are used. High strength swivel hanger bars can easily be nailed to joists. Maximum hole cutout is 3 5/8". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts, four 3/4" knockouts with pry-out knockout slots. 4 Romex pryouts with strain relief.

Hanger Bars: Pre-installed swivel hanger bars with TrueNail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

Plenum: EL362AJICA, Speciality Plenum Modification, 2 knockouts for wiring. Suitable for Plenum Installations in environmental air-handling spaces per UL 2043. Luminaire construction contains no polymeric materials exposed to the airstream within the plenum.

Dimmability: Dimmability based on lamp.

Lamp: Designed for use with ELCO 3" PEX Diecast Trims and KotoTM LED module

Listings:

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

- cUL and UL Listed
- UL Listed (US and Canada) for Damp Location.
- UL Listed (US and Canada) for Wet Location with select trims.
- UL Listed (US and Canada) for Feed Through.
- UL Listed (US and Canada) for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.