ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ SYLO™ DIRECT MOUNT WITH KOTO™ FOCUS MODULE

Direct Mount · 3″ · 3 finishes



Adjustable Focus: 18° to 50° with a simple twist of the snoot

FEATURES

- Modern Monopoint Die-Cast aluminum fixture for easy maintenance and upgrades
- Standard Fixtures or Fixtures with Stems (12", 24", 36", 48", and 60") available
- Fits 3 ½″ and 4″ Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- 90° tilt, 358° rotation
- Energy Star Certified. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- Integrated 120V Dimmable Driver Triac/ELV
- 95+ CRI color rendering
- Covered by U.S. PATENTS and Patents Pending

SPECIFICATIONS

Wattage	10.5 · 12.5 · 16.8 W
Lumens	720 · 750 · 770 · 800 · 830 · 860 · 950 · 1250 lm
Voltage	120V · 120-277V
Color temp.	2700K · 3000K · 3500K · 4000K · Sunset
Dimming	Triac/ELV · 0-10V/Triac/ELV
Lamp type	LED
Beam angle	Adjustable Beam 18° - 50°
CRI	95+
Aperture	3"
Mounting style	Direct Mount
Module	750 lm (10.5W) · 950 lm (12.5W) · 1250 lm (16.8W) · 770 lm - 860 lm (10.5W)

FINISHES



White



Black



Silver

Item page
elcolighting.com/items/3-sylo-direct-mount-koto-focus-module
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

3″ Koto Sylo™ Direct Mount

© ELCO Lighting 2026. All rights reserved • Rev. 11 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **3" Sylo™ Direct Mount with Koto™ Focus Module** item number (Select one) Example: **E36DB-0727-FC** Your item number:

ITEM	VOLTAGE	FINISH	MODULE	CCT	MOUNTING STYLE	BEAM ANGLE
E36	120V **D** 120-277V	**W** White **B** Black **S** Silver	**-07** 750 lm (10.5W) **-09** 950 lm (12.5W) **-12** 1250 lm (16.8W) **-07** 770 lm - 860 lm (10.5W)	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[1, 2]	**D** Direct Mount	**-FC** Adjustable Beam 18° - 50°

[1] Available in -09, -11, -13, -15, & -18 lumen outputs [2] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless module installation.

Electrical: Module connects to 120V power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens:

ELK0727 770 lm/10.5W/2700K **ELK0730** 800 lm/10.5W/3000K
ELK0735 830 lm/10.5W/3500K **ELK0740** 860 lm/10.5W/4000K

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing an integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: For a full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. UL Listed (US and Canada) for Wet Location with Wet location trims. RoHS Compliant. Meets California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 11 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.