ELCO Lighting

Project Name:

Fixture Type:

Date:

3″ SYLO™ TRACK HEAD WITH KOTO™ FOCUS MODULE

Track Head · 3″ · 3 finishes

Adjustable Focus: 18° to 50° with a simple twist of the snoot



FEATURES

- Modern Track Head Die-Cast aluminum fixture for easy maintenance and upgrades
- Standard Fixtures or Fixtures with Stems (12″) available
- Works with Single and Two Circuit Track
- Sunset option dims from 3000K to 1800K
- 90° tilt, 358° rotation
- ENERGY STAR compliant. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- Standard H style, J & L Styles available
- Integrated 120V Dimmable Driver Triac/ELV
- 95+ CRI color rendering
- Covered by U.S. PATENTS and Patents Pending

DIMENSIONS



Dimensions with Stem



Dimensions with Stem

SPECIFICATIONS

Wattage	10.5W
Lumens	720 · 750 · 800 · 830 · 860 lm
Voltage	120V
Color temp.	2700K · 3000K · 3500K · 4000K · Sunset
Dimming	Triac/ELV
Lamp type	LED
Beam angle	18° - 50° · Adjustable Beam 18° - 50°
CRI	95+
Aperture	3"
Mounting style	Track Head
Module	770 lm - 860 lm (10.5W) · 950 lm (12.5W) · 1250 lm (16.8W)
Length	Standard · 12" Stem

FINISHES



White



Black



Silver

Item page
elcolighting.com/items/3-sylo-track-head-koto-focus-module
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ and 3″ Koto Sylo™ Track Head

↓ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **3" Sylo™ Track Head with Koto™ Focus Module** item number (Select one) Example: **E36TW-0727-FC** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	CCT	BEAM ANGLE	LENGTH
E36	**T** Track Head	**W** White **B** Black **S** Silver	**-07** 770 lm - 860 lm (10.5W) **-09** 950 lm (12.5W) **-12** 1250 lm (16.8W)[1]	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[2, 3]	**-FC** 18° - 50° Adjustable Beam 18° - 50°	Standard **-12** 12" Stem

[1] Stem is not field cuttable [2] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [3] Available with -07 lumen output only. 120V, Triac/ELV only.

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless module installation.

Electrical: Module connects to 120V power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens:

ELK0727 770 lm/10.5W/2700K **ELK0730** 800 lm/10.5W/3000K
ELK0735 830 lm/10.5W/3500K **ELK0740** 860 lm/10.5W/4000K

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing an integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: For a full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: RoHS Compliant. Meets California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 09 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.