ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ 120/277/347V LED RECESSED GIMBAL DOWNLIGHT WITH 5-CCT SWITCH



Canless LED · Round · 6″

Our 4" Dimmable LED Recessed Gimbal Downlight is designed for quick and easy installation without a housing for both new construction and remodel applications, giving you the options you are looking for in one fixture.

ITEM NUMBER **ERT413CT5DXW**

FEATURES

•Adjustable Gimbal offers 25° tilt range
•IC Airtight for use with direct contact to insulation.
•Lumens (Wattage): 650 lm (10W)
•Designed to fit in plenums as shallow as 3″.
•Eliminates the need for housing.
•OPTIONAL mounting frame available: E4LF1, E246LF1 or EMP4.
•Remodel applications require no additional accessories.
•Wet Location allows for use indoors or outdoors.
•ETL listed
•Includes driver and Jbox.

DIMENSIONS



SPECIFICATIONS

Wattage	10W
Lumens	650 lm
Voltage	120-277-347V
Color temp.	2700K-5000K
Dimming	0-10V/Triac/ELV
Lamp type	LED
CRI	90+
Aperture	6"
Shape	Round

FINISHES

White

Item page
elcolighting.com/items/4-120277347v-led-recessed-gimbal-downlight-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Ply™ 0-10V Dimmable Retrofits · 4″ Elm™

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

TECHNICAL DETAILS

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: IC-rated driver and fixture are tested and approved for direct contact with insulation. Plenum-rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High-strength steel spring clip for easy installation. Maximum hole size should not exceed 4 1/2" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Driver connects directly to 120/277/347V power supply. Standard input wattage is 10W, 65 lumens per watt.

Dimmability: Works with 120/277/347V dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatability List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation.

Warranty: 5-year limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.