ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ CANLESS KOTO™ IC NEW CONSTRUCTION FRAME

Frames & Power Packs

IC Rated for direct contact with insulation. Easy-to-remove driver included on frame. To be used with Canless Koto™ LED Modules.



FEATURES

- Must be used with Canless Koto™ LED Modules
- IC Rated for direct contact with insulation
- Easy-to-remove driver included
- Driver specified for 120V (Triac/ELV) or 120/277V (0-10V/Triac/ELV)

DIMENSIONS



SPECIFICATIONS

Wattage	10.5W
Lumens	950 lm
Voltage	120V · 120-277V
Dimming	Triac/ELV · 0-10V/Triac/ELV
Emergency option	No Emergency Backup · 90 min. Emergency Battery Backup

Item page
elcolighting.com/items/4-canless-koto-ic-new-construction-frame
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Canless Koto™

↓ Dimmer compatibility list
elcolighting.com · Dimmer Canless Koto™ System

PRODUCT NUMBER BUILDER

Specify **4″ Canless Koto™ IC New Construction Frame** item number (Select one) Example: **E4KCL10IC** Your item number:

ITEM	VOLTAGE	EMERGENCY OPTION
E4KCL10		
	IC 120V **ICDX** 120-277V	No Emergency Backup **-EM** 90 min. Emergency Battery Backup

TECHNICAL DETAILS

Construction: IC rated for direct contact with insulation. For use in IC and Non-IC conditions.

Installation: High strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Hanger Bars: Pre-Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical: Driver is rated for 120V or 120/277V input. High Efficiency

© ELCO Lighting 2026. All rights reserved • Rev. 26 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

driver with a power factor > 0.95.

Dimmability: Option ELV/TRIAC dimming or 3 in 1 dimming: Triac, ELV and 0-10V dimming can be specified.

© ELCO Lighting 2026. All rights reserved • Rev. 26 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.