ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ FLOATING ADJUSTABLE EYEBALL DOWNLIGHT WITH 5-CCT SWITCH



Canless LED · Round · 3 finishes

The innovative 4″ Floating Eyeball offers 360˚ rotation and a 90˚ tilt range for added versatility.

FEATURES

- 9W / 780 lm
- IC Rated for direct contact to insulation
- CRI 90+
- 120V
- ETL Listed for damp locations
- CA Title 24 compliant
- Dimmable Triac/ELV
- For EM Backup use KEM-ERT
- 28° beam spread

DIMENSIONS



SPECIFICATIONS

Wattage	9W
Lumens	780 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	28°
CRI	90+
Shape	Round

FINISHES


White


Bronze


Black

Item page
elcolighting.com/items/4-floating-adjustable-eyeball-downlight-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Elm™

⬇ Dimmer compatibility list
elcolighting.com · Elm Dimmer Compatibility

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **4" Floating Adjustable Eyeball Downlight with 5-CCT Switch** item number (Select one) Example: **ERT416CT5W** Your item number:

ITEM	CCT	FINISH
ERT416	**CT5** 2700K-5000K	**W** White **BZ** Bronze **B** Black

TECHNICAL DETAILS

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: Aluminum die-cast trim with durable powdercoat finish. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template for proper trim installation.

Electrical: Included driver connects directly to 120V power supply. Standard input wattage is 9W, 85 lumens per watt.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatability List.

Listings: ETL Listed for Damp Locations. IC-Rated for direct contact with insulation. Air Tight certified in accordance with ASTM E283-2004. California Title 24 Compliant (JA8-2025-E)

Warranty: 5-year limited warranty.





© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.