ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ KOTO SYLO™ PENDANT


Pendant · 4″ · 3 finishes



FEATURES

- Modern Pendant Die-Cast aluminum fixture for easy maintenance and upgrades
- Available with 120″ Field Cuttable Cable or Stems (12", 24", 36", 48", 60", 72" and 84")
- Includes Standard 38° lens, with 25° and 60° lenses. Optional: 18° & 90° lenses available.
- Fits 3 ½″ and 4″ Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- Human Centric option dims from 4000K to 2200K
- Tunable White option dims from 1800K to 4000K
- Energy Star Certified. Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70

DIMENSIONS



SPECIFICATIONS

Wattage	10.5 · 12.5 · 5 · 14.7 · 23 · 29 · 11.5 · 18.9 · 21 W
Lumens	350 · 750 · 825 · 880 · 950 · 1000 · 1150 · 1350 · 1500 · 1800 · 2000 · 2500 · 3000 lm
Voltage	120V · 120-277V
Color temp.	2400K · 2700K · 3000K · 3500K · 4000K · Sunset · Human Centric · 2700K-5000K · 1800K-4000K · Tunable White · Turtle Friendly Amber
Dimming	120V Triac/ELV · 120/277V, 0-10V/Triac/ELV · DALI 2, 120/277V · Triac/ELV · 0-10V/Triac/ELV · DALI 2 Controlled
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 10° · 90°
CRI	95+
Aperture	4"
Mounting style	Pendant
Module	350 · 750 · 950 · 1150 · 1350 · 1500 · 1800 · 2000 · 2500 · 3000 · 825 · 880 · 1000 lm
Length	120" Cable Mount · 12" Stem · 24" Stem · 36" Stem · 48" Stem · 60" Stem · 72" Stem · 84" Stem

FINISHES



Item page
elcolighting.com/items/4-koto-sylo-pendant
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Koto Sylo™ Pendant

↓ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **4" Koto Sylo™ Pendant** item number (Select one) Example: **E42PW-0727** Your item number:

ITEM	MOUNTING STYLE	FINISH	MODULE	CCT	DIMMING	BEAM ANGLE	LENGTH
E42	**P** Pendant	**W** White **B** Black **S** Silver	**-03** 350 lm (5W)[1, 2] **-07** 750 lm (10.5W) **-09** 950 lm (10.5W) **-11** 1150 lm (12.5W) **-13** 1350 lm (12.5W) **-15** 1500 lm (14.7W) **-18** 1800 lm (18.9W) **-20** 2000 lm (21W) **-25** 2500 lm (23W)[3, 4] **-30** 3000 lm (29W)[3, 4] **-08** 825 lm (10.5W)(CT5 Only) **-08** 880 lm (11.5W)(41TA Only)[5] **-10** 1000 lm (12.5W)(CT5 Only)[1, 6]	**24** 2400K **27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[7, 8] **HC** Human Centric[1, 9, 10] **CT5** 2700K-5000K[1, 11] **4T** 1800K-4000K[12] Tunable White **AMD** Turtle Friendly Amber[13, 14]	**D** 120/277V, 0-10V/Triac/ELV **A** DALI 2, 120/277V	38° **-S** 18° **-N** 25° **-W** 60° **-T** 10°[1, 15] **-E** 90°[16]	120" Cable Mount[17] **-12** 12" Stem[18] **-24** 24" Stem[18] **-36** 36" Stem[18] **-48** 48" Stem[18] **-60** 60" Stem[18] **-72** 72" Stem[18] **-84** 84" Stem[18]

No separate code: Dimming: 120V Triac/ELV, Triac/ELV, 0-10V/Triac/ELV, DALI 2 Controlled

[1] Available as 120V, Triac/ELV only [2] Available with 2400K, 2700K and 3000K Color Temperature Only [3] Available as 120/277V, 0-10V/Triac/ELV only [4] Available with 2700K, 3000K, 3500K, & 4000K Color Temperature Only [5] Available with Tunable White color temperature only [6] Available with CT5 color temperature only [7] Available with -09, -11, -13, -15 and -18 lumen outputs only [8] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [9] Available with 1150 lumen (-11) outputs only [10] Human Centric, Dim to Warm technology, automatically transitions from 4000K to 2200K when dimmed [11] Available with -08 and -10 lumen outputs only [12] Available with -AL option only, Dali 2 dimmable Tunable White [13] Available with -03, -07, -09 and -11 lumen outputs only [14] Turtle friendly [15] Available with 350 and 750 lumen, 2700K and 3000K options only [16] 90° Frosted Reflector [17] 120 inch field cuttable cable [18] Stem is not field cuttable

TECHNICAL DETAILS

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless module installation.

Electrical: Module connects to 120V power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens:

0327 2700K/442.8 lm/5W **0330** 3000K/461.2 lm/5W

0727 2700K/770 lm/10.5W **0730** 3000K/800 lm/10.5W **0735** 3500K/830 lm/10.5W **0740** 4000K/860 lm/10.5W

08CT5 2700K/728.5 lm/10.5W **08CT5** 3000K/886 lm/10.5W **08CT5** 3500K/902 lm/10.5W **08CT5** 4000K/920 lm/10.5W **08CT5** 5000K/931 lm/10.5W

0927 2700K/912 lm/10.5W **0930** 3000K/950 lm/10.5W **0935** 3500K/990 lm/10.5W **0940** 4000K/1030 lm/10.5W **09SD** Sunset/940 lm/10.5W

10CT5 2700K/908 lm/12.5W **10CT5** 3000K/1012 lm/12.5W **10CT5** 3500K/1038 lm/12.5W **10CT5** 4000K/1040 lm/12.5W **10CT5** 5000K/1032 lm/12.5W

1124 2400K/730 lm/12.5W **1127** 2700K/1068 lm/12.5W **1130** 3000K/1112 lm/12.5 **1135** 3500K/1156 lm/12.5W **1140** 4000K/1202 lm/12.5W **11SD** Sunset/1050 lm/12.5W **11HC** Human Centric/1050 lm/12.5W

1327 2700K/1260 lm/12.5W **1330** 3000K/1312 lm/12.5W **1335** 3500K/1365 lm/12.5W **1340** 4000K/1420 lm/12.5W

1527 2700K/1439 lm/14.7W **1530** 3000K/1501 lm/14.7W **1535** 3500K/1565 lm/14.7W **1540** 4000K/1627 lm/14.7W

Emergency Battery Backup: Integral EM Test Switch on Cylinder. The fixture becomes 120V only.

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Dimmability: For full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: ETL Listed, ETL Listed for Damp Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.