ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ LED IC AIRTIGHT SLOPED CEILING REMODEL HOUSING

Housing

ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 6/12 (26.5°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.

ITEM NUMBER **EL470RICA**



FEATURES

- Allows for direct contact with insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- California Title 24 (JA8-2025-E).

DIMENSIONS



SPECIFICATIONS

Wattage	14W
Voltage	120V
Component style	Sloped Ceiling

Item page
elcolighting.com/items/4-led-ic-airtight-sloped-ceiling-remodel-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Slant™ · 4″ Koto™ Sloped Ceiling

Dimmer compatibility list

elcolighting.com · Dimmer Compatibility List

TECHNICAL DETAILS

Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Housing adjusts to accommodate up to 3/4” ceiling thickness.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. Template for hole cutout is provided with each housing. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2” trade size conduit knockouts and One 3/4” knockout. Four true pry-out knockout slots for easy Romex installation.

Electrical: Connection is rated for 120V input.

Compatible Trims: EL423CT5W, EL423CT5BZ, EL425CT5W.

Listings:

- UL Listed (US and Canada) for Damp Location.
- UL Listed (US and Canada) for Direct Contact with Insulation and Combustible Material.
- UL Listed (US and Canada) for Feed Through.
- AirTight Per ASTM E-283.
- California Title 24 (JA8-2025-E).

Warranty: ELCO Products are built to last. 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 22 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.