ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ LED SLOPED ROUND REGRESSED GIMBAL WITH 5-CCT SWITCH

Canless LED · Round · 4″



Our 4" LED Sloped Regressed Gimbal Downlight is designed for quick and easy installation without a housing for both new construction and remodel applications, gives you the options you are looking for in one fixture.

ITEM NUMBER **ERT425CT5W**

FEATURES

•Adjustable Regressed Gimbal for Wall Wash and Sloped Ceiling
•38˚ beam with 25˚ tilt and 360˚ rotation
•IC Airtight for use with direct contact to insulation
•Designed to fit in plenums as shallow as 3″.
•Eliminates the need for housing.
•Designed for use with 2/12 up to 12/12 sloped ceilings.
•Remodel applications require no additional accessories.
•Wet Location for indoor use only.
•ETL listed, Energy Star, Title 24 JA8-2025-E
•Includes driver and Jbox.

DIMENSIONS



SPECIFICATIONS

Wattage	8W
Lumens	510 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	38°
CRI	90+
Aperture	4"
Shape	Round

FINISHES

White

Item page
elcolighting.com/items/4-led-sloped-round-regressed-gimbal-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Elm™

⬇ Dimmer compatibility list
elcolighting.com · Elm System LED Downlights Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 22 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

TECHNICAL DETAILS

Construction: IC rated driver and fixture are tested and approved for direct contact with insulation. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation. Maximum hole size should not exceed 4 3/4″ for this product. Suitable installation for t-grid and drop ceiling applications. Designed for use with 2/12 up to 12/12 sloped ceilings.

Electrical: Standard input wattage is 8W, 63.75 lumens per watt.

Dimmability: Works with 120V Triac/ELV type dimmers. For full list of dimmers, refer to the Dimmer Compatability List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation.

Warranty: 5-year limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 22 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.