ELCO Lighting

Project Name:

Fixture Type:

Date:

4″ ULTRA SLIM LED ROUND PANEL LIGHT WITH 5-CCT SWITCH

Canless LED · Round · 3 finishes



These unique 4" ultra slim panel lights designed for quick and easy installation without a housing for both new construction and remodel applications, gives you the options you are looking for in one fixture.

FEATURES

- IC Airtight for use with direct contact to insulation.
- Designed to fit in plenums as shallow as 2″.
- Eliminates the need for housing.
- OPTIONAL mounting frame available: E4LF1 or EMP4.
- Remodel applications require no additional accessories.
- Wet Location allows for use indoors or outdoors.
- CA Title 24 and ENERGY STAR Compliant.
- Includes driver and Jbox.
- For EM Backup use KEM-ERT

DIMENSIONS



SPECIFICATIONS

Wattage	9 · 12 W
Lumens	9W / 500 lm · 12W / 984lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
CRI	90+
Shape	Round

FINISHES


White


Black


Bronze

Item page
elcolighting.com/items/4-ultra-slim-led-round-panel-light-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Elm™

Dimmer compatibility list

elcolighting.com · Elm System CCT LED Downlights Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **4" Ultra Slim LED Round Panel Light with 5-CCT Switch** item number (Select one) Example: **ERT411CT5W** Your item number:

ITEM	LUMENS	CCT	FINISH
ERT4	**11** 9W / 500 lm **12** 12W / 984lm	**CT5** 2700K-5000K	**W** White **B** Black **BZ** Bronze

No separate code: Lumens: 500 lm, 984 lm

TECHNICAL DETAILS

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: IC rated driver and fixture are tested and approved for direct contact with insulation. Aluminum die-cast trim ring with durable powdercoat finish preventing rust and paint cracking. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation. Maximum hole size should not exceed 4 1/4" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Driver connects directly to 120V power supply. Standard input wattage is 9W (ERT411) or 12W (ERT412).

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatability List.

Listings: ETL Listed for Wet Locations. Meets ENERGY STAR® requirements. IC-Rated for direct contact with insulation. California Title 24 Compliant.

Warranty: 5-year limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.