ELCO Lighting

Project Name:

Fixture Type:

Date:

5″ IC AIRTIGHT NEW CONSTRUCTION HOUSING WITH GU24 BASE SOCKET

Housing · 5 1/2″



ITEM NUMBER **EL5ICA-G24**

FEATURES

•Airtight Housing for insulated ceilings.
•Adjustable socket bracket.
•Lamp: Self ballasted CFL, GU24 base.
•Meets CA Title 24 standards with qualified lamps.
•UL Listed (US and Canada) for damp location and for feed through.

DIMENSIONS



SPECIFICATIONS

Wattage	27W
Voltage	120V
Lamp type	GU24
Aperture	5 1/2"

Item page
elcolighting.com/items/5-ic-airtight-new-construction-housing-gu24-base-socket
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

5″ Medium Base Housings & Trims

TECHNICAL DETAILS

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Aluminum housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. High strength hanger bars can easily be nailed to joists. Maximum hole cutout is 5 1/2". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size pryout conduit knockouts, 4 Romex pryouts with strain relief.

Hanger Bars: Pre-installed hanger bars with True Nail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-grids. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housing with the joists.

Electrical:

- Input Voltage: 120V AC.
- Thermally protected against improper lamping.

Trims: Compatible with ELCO 5" Line Voltage PAR trims.

Lamp: Designed for use with 27W MAX Self ballasted CFL, GU24 base.

Listings:

- UL Listed (US and Canada) for Damp Location.
- UL Listed (US and Canada) for Feed Through.
- **c**UL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2025-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.