ELCO Lighting

Project Name:

Fixture Type:

Date:

5"/6" LED DEEP REFLECTOR INSERTS WITH 5-CCT SWITCH



Light Engine · Round · 5″ · 6″ · 3 finishes

This unique LED recessed downlight gives you the options you are looking for in one fixture. The manual switch located on the driver allows you to choose between 2700K (880 lm), 3000K (960 lm), 3500K (1040 lm), 4000K (1060 lm) or 5000K (1080 lm).

FEATURES

- Switch from a 2700K to 5000K by using manual switch on driver
- Soft white lens provides smooth lumen distribution
- Deep set LED trim reduces glare while providing area illumination
- Includes Medium Base Adapter (PSA30) for retrofitting existing E26 Base housings
- Title 24 JA8-2025-E Compliant
- Life span of 50,000 hours L70
- Delivered Lumens: 880lm (27K), 960lm (30K), 1040lm (35K), 1060lm (40K), 1080lm (50K)

DIMENSIONS



SPECIFICATIONS

Wattage	15W
Lumens	1000 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
CRI	90+
Aperture	5" · 6"
Shape	Round

FINISHES

White | Haze with White Ring | Chrome with White Trim

Item page
elcolighting.com/items/56-led-deep-reflector-inserts-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

5″ LED Housings and Inserts · 6″ LED Housings and LED Inserts

↓ Dimmer compatibility list
elcolighting.com · 6" LED Inserts Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **5"/6" LED Deep Reflector Inserts with 5-CCT Switch** item number (Select one) Example: **EL625CT5W** Your item number:

ITEM	FINISH
EL625CT5	
	C Chrome with White Trim

No separate code: Finish: White, Haze with White Ring

TECHNICAL DETAILS

Optics: Soft white lens provides smooth lumen distribution.

Construction: For use in IC and Non-IC housings. Spun Metal for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Includes PSA30 medium base adapter for retrofitting existing housings. Quick connect for use with ELCO housings EL570ICA, EL570RICA, EL56FICA, EL560ICA, EL560RICA, EL770ICA, EL770RICA, EL760ICA, EL760RICA, EL76FICA. Can be used in IC and non-IC housings.

Electrical: Driver connects to120V power supply. High Efficiency driver with a power factor > 0.9. Start time of less than .75 seconds.

LED Technology: 90+ CRI color rendering. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integral heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Wet Location. RoHS Compliant. Title 24 JA8-2025-E Compliant.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.