ELCO Lighting

Project Name:

Fixture Type:

Date:

6" LED BAFFLE INSERTS WITH 5-CCT SWITCH

Light Engine · Round · 5″ · 6″



This unique LED recessed downlight gives you the options you are looking for in one fixture. The manual switch located on the driver allows you to choose between 2700K, 3000K, 3500K, 4000K or 5000K.

ITEM NUMBER **EL670CT5W**

FEATURES

- Switch from a 2700K to 5000K by using manual switch on driver
- Soft white lens provides smooth lumen distribution
- Works with 5″ or 6″ dedicated recessed housings
- Medium base to quick connect adapter included (PSA30)
- UL Listed (US and Canada) for wet locations
- Title 24 JA8-2025-E Compliant
- Dimmable Triac/ELV

DIMENSIONS



SPECIFICATIONS

Wattage	10W
Lumens	700 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
CRI	90+
Aperture	5" · 6"
Shape	Round

FINISHES

White

Item page
elcolighting.com/items/6-led-baffle-inserts-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

5″ LED Housings and Inserts · 6″ LED Housings and LED Inserts

↓ Dimmer compatibility list

elcolighting.com · 6" LED Inserts (2) Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

TECHNICAL DETAILS

Optics: Soft white lens provides smooth lumen distribution.

Construction: For use in IC and Non-IC Housings. Spun Metal for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Quick connect for use with ELCO housings EL570ICA, EL570RICA, EL56FICA, EL560ICA, EL560RICA, EL770ICA, EL770RICA, EL760ICA, EL760RICA, EL76FICA. Can be used in IC and Non-IC Housings.

Electrical: Driver connects to120V power supply. High Efficiency driver with a power factor > 0.9. Start time of less than .75 seconds.

LED Technology: 90+ CRI color rendering. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integral heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for wet location. Title 24 JA8-2025-E Compliant.

Warranty: ELCO Products are built to last. 5-year Limited warranty

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.