ELCO Lighting

Project Name:

Fixture Type:

Date:

6″ NEW CONSTRUCTION 2-HOUR FIRE RATED IC AIRTIGHT HOUSING

Housing · 6″



6" fire rated new construction LED housing with quick connect. Compatible with 6" LED inserts. 2-hour fire rated, can include step-down transformer.

FEATURES

- IC Airtight for direct contact with insulation.
- UL Listed (US and Canada) for 2-Hour Fire Resistance.
- Integrated Non-combustible insulation acts as a sound barrier minimizing sound transfer between floors.
- Meets Title 24 JA8-2025-E requirements.
- STC/IIC Sound Rated
- Trims and inserts sold separately.
- For use with ceiling constructions: L505, L511, L536, L538, L541, L556, L577, M500, M510, M521 and M543.

DIMENSIONS



SPECIFICATIONS

Wattage	24 · 22 W
Voltage	120V · 277V · 120-277V
Dimming	Triac/ELV
Aperture	6"
Emergency option	No Emergency Backup · Emergency Battery Backup

ITEM NUMBERS

ITEM NUMBER	WATTS	VOLTAGE	DIMMING	EMERGENCY OPTION
EL76FICA	22W	120-277V	Triac/ELV	No Emergency Backup
EL76FICA-7	22W	277V	—	No Emergency Backup
EL76FICA-EM5	24W	120-277V	Triac/ELV	Emergency Battery Backup

Item page
elcolighting.com/items/6-new-construction-2-hour-fire-rated-ic-airtight-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

6″ Standard Koto™ · 6″ Poplar™ · 6″ LED Housings and LED Inserts · 6″ Koto™ Aim

TECHNICAL DETAILS

Construction:

- Double wall IC rated for direct contact with insulation. For use in IC and non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- For use with ceiling constructions: L505, L511, L536, L538, L541, L556, L577, M500, M510, M521, and M543.

© ELCO Lighting 2026. All rights reserved • Rev. 13 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

Installation:

- Designed for ceiling plenums where 2x8 joists or taller are used.
- High strength hanger bars can easily be nailed to joists.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4” knockouts, Seven 1/2” trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Hanger Bars: Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Emergency Battery Pack: Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

Lamp: Designed for use with ELCO 6" LED inserts, LED modules, or PSA37 with 6" MR16 trims.

Listings: UL Listed (US and Canada) for Damp Location and for Wet Location with select trims. UL Listed (US and Canada) for Direct Contact with Insulation and Combustible Material. UL Listed (US and Canada) for Feed Through. Sound rated.

© ELCO Lighting 2026. All rights reserved • Rev. 13 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.