ELCO Lighting

Project Name:

Fixture Type:

Date:

# 6″ REMODEL FRAME WITH DRIVER

**Housing · 6 1/4″**



## FEATURES

- Optional 90 minutes, 120/277 VAC, 60Hz Emergency Backup.
- USA designed and assembled.
- LED Light Engine sold separately (see Compatible Trims).
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## DIMENSIONS




## SPECIFICATIONS

| | |
|---|---|
| Lumens | 850 · 1250 · 1600 · 2000 · 3000 · 4000 · 6000 lm |
| Voltage | 120-277V · 120V |
| Dimming | Triac/ELV/0-10V · Sunset (warm dim) |
| Power factor | >0.9 |
| Aperture | 6 1/4" |
| Generation | Gen 2 · Gen 1 |
| Emergency option | No Emergency Backup · 8W Emergency Backup · 12W Emergency Backup |

**Item page**
elcolighting.com/items/6-remodel-frame-driver
Every item number, IES files, downloads and the latest revision.

## PART OF THESE FAMILIES

6″ Laurel™

⬇ Dimmer compatibility list
elcolighting.com · Dimmer Compatibility List


© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

## PRODUCT NUMBER BUILDER

Specify **6" Remodel Frame with Driver** item number (Select one) Example: **E6LRU08D2** Your item number:

| ITEM | VOLTAGE | LUMENS | DIMMING | GENERATION | EMERGENCY OPTION |
|---|---|---|---|---|---|
| | | | | | |
| **E6LR** | **U** 120-277V<br>120V | **08** 850 lm<br>**12** 1250 lm<br>**16** 1600 lm<br>**20** 2000 lm<br>**30** 3000 lm<br>**40** 4000 lm<br>**60** 6000 lm | **D** Triac/ELV/0-10V<br>**S** Sunset (warm dim) | **2** Gen 2<br>Gen 1 | No Emergency Backup<br>**EM1** 8W Emergency Backup<br>**EM2** 12W Emergency Backup |

## TECHNICAL DETAILS

**Construction:**

Constructed from 16 gauge galvanized steel for commercial building applications.

**Installation:**

Remodel clips hold housing sturdily into place.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and four pry-out knockout slots for easy romex installation.

**Electrical:**

•Driver is rated for 120V and 277V input (120/277V).
•High Efficiency driver with a power factor > 0.9.
•Can be specified with Lutron drivers for specific applications.

**Dimmability:**

•3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
•0-10V dimming down to 5% with a compatible dimmer.
•Flicker-Free Dimming.
•Can be specified with Lutron drivers for 0.1% and 1% dimming.
•For a full list of dimmers refer to the Dimmer Compatibility List.

**Listings:** cULus Listed for Damp Location. cULus Listed for Wet Location with select trims. cULus Listed for Direct Contact with Insulation and Combustible Material for units up to 2000 lm. cULus Listed for Feed Through.

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.


© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.