ELCO Lighting

Project Name:

Fixture Type:

Date:

6″ SHALLOW LED 120V ROUND REFLECTOR INSERT WITH 5-CCT SWITCH



Canless LED · Round · 6″

Our 6" LED Recessed Downlights are designed for quick and easy installation without housing for both new construction and remodel applications, gives you the options you are looking for in one fixture.

FEATURES

- IC Airtight for use with direct contact to insulation.
- Designed to fit in plenums as shallow as 3″.
- Eliminates the need for housing.
- OPTIONAL mounting frame available.
- Remodel applications require no additional accessories.
- Wet Location allows for use indoors or outdoors.
- Title 24 JA8-2025-E Compliant
- Includes driver and Jbox.

DIMENSIONS



SPECIFICATIONS

Wattage	12W
Lumens	900 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
CRI	90+
Aperture	6"
Shape	Round

FINISHES

White

Item page
elcolighting.com/items/6-shallow-led-120v-round-reflector-insert-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

6″ Elm™

Dimmer compatibility list

elcolighting.com · Elm System CCT LED Downlights Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **6" Shallow LED 120V Round Reflector Insert with 5-CCT Switch** item number (Select one) Example: **ERT615CT5W** Your item number:

ITEM	CCT	FINISH
ERT615		
	CT5 2700K-5000K	**W** White

TECHNICAL DETAILS

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: IC rated driver and fixture are tested and approved for direct contact with insulation. Plenum-rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut-out template provided for accurate hole size for proper trim installation. The maximum hole size should not exceed 6" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Standard input wattage is 12W, 75 lumens per watt.

Dimmability: Works with 120V Triac/ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatability List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation. Title 24 JA8-2025-E Compliant.

Warranty: 5-year limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.