ELCO Lighting

Project Name:

Fixture Type:

Date:

6″ SLOPED CEILING MEDIUM BASE NON-IC REMODEL HOUSING

Housing



ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 6/12 (26.5°). Fits in 2" x 8" joist construction.

ITEM NUMBER **EL900RT**

FEATURES

- Non-IC Remodel Slope Ceiling Housing.
- Integral thermal protector guards against improper lamping.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Socket: Medium base E26.
- Compatible with Medium Base Incandescent, CFL or LED Lamp MAX. 150W. Works with LED Quick-Connect Inserts with PSA30 Socket Adapter.

DIMENSIONS



SPECIFICATIONS

Wattage	150W
Voltage	120V
Lamp type	Medium Base (E26)

Item page
elcolighting.com/items/6-sloped-ceiling-medium-base-non-ic-remodel-housing
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

6″ Sloped Housings and Trims · 6″ Slant™ Housings and Trims

Dimmer compatibility list

elcolighting.com · Sloped Ceiling Dimmer Compatibility List

TECHNICAL DETAILS

Construction:

- Designed for use in 2/12 to 6/12 sloped ceiling where insulation is kept 3″ away from fixture housing.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2” trade size conduit knockouts and One 3/4” knockout. Four true pry-out knockout slots for easy Romex installation.

Electrical:

- Rated for 120V or 277V input.
- For 277V step down to 120V housing consult factory.

Trims: Compatible with ELCO Line Voltage Slope Trims.

Listings: UL Listed (US and Canada) for Damp Location.
UL Listed (US and Canada) for Feed Through.

© ELCO Lighting 2026. All rights reserved • Rev. 22 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.