ELCO Lighting

Project Name:

Fixture Type:

Date:

BIRCH™ PRO LED MODULE WITH 5-CCT SWITCH (750 LM-1500 LM)

Light Engine




The beautifully designed die-cast module houses powerful and advanced LED technology to provide increased durability and outstanding illumination. Works with 4", 6" & 8" Birch Commercial Frames, Remodel, Retrofits and Twist-On Trims.

ITEM NUMBER **ELB15RCT5ICA**

FEATURES

- **IC Rated** for direct contact with insulation, for use in IC and Non-IC applications
- Select Color Temperature (2700K to 5000K) and Lumen Output (750 lm to 1500 lm) by using manual switch on module
- Adjustable Focus Beam Angle allows for manual beam angle adjustment from 25° to 45° range with the ease of a twist
- Twist-On mechanism to lock the module easily to any size trim
- Encased Quick Connector for easy module installation
- Works in 4″, 6″, and 8″ Commercial Frames, Remodel and Retrofit applications
- 120/277V input with 0-10V dimming
- 90+ CRI color rendering
- Meets Energy Star Requirements
- ETL listed for damp location with adjustable trims and for wet location with fixed trims
- Life span of 50,000 hours L70

DIMENSIONS



SPECIFICATIONS

Wattage	9W / 13W / 18W
Lumens	850 lm / 1150 lm / 1500
Voltage	120-277V
Color temp.	2700K-5000K
Dimming	0-10V
Lamp type	LED
Beam angle	30° to 70°
CRI	90+

Item page
elcolighting.com/items/birch-pro-led-module-5-cct-switch-850-lm-1500-lm
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4″ Birch™ Round · 4″ Birch™ Square · 6″ Birch™ Round · 8″ Birch™ Round

⬇ Dimmer compatibility list
elcolighting.com · Birch System Dimmer List

TECHNICAL DETAILS

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with Encased Quick Connect. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist-On design for tool-less trim installation, for use with Birch™ Trims. Can be used in 4″, 6″, and 8″ Commercial Frames and Remodel/Retrofit applications with Encased Quick Connect base. For use in IC and Non-IC applications.

Electrical: Module connects to 120/277V power supply. High

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Color Rendering Index of 90+. Lumen Maintenance of 50,000 hours L70 Life span. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Dimmability: 0-10V dimmable. Dims down to 5%. For a full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: ETL Listed for Damp Location with adjustable trims and for Wet Location with fixed trims.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.