ELCO Lighting

Project Name:

Fixture Type:

Date:

IBIS™ LED STEP LIGHT WITH ANGLED LOUVER (HORIZONTAL)

Fixture · Rectangular · 5 finishes



ELCO's Ibis Collection consists of diecast wet location mini LED Step Lights which are offered in 2W or 3W, 3000K or 4000K, 120V or 12V AC/DC in round or rectangle with an Angled Louver, Open Frame Lens or Scoop Faceplate.

FEATURES

- Single Piece Diecast aluminum faceplate.
- Powder Coated Faceplate.
- Horizontal Mounting.
- Integrated LED board and driver.
- Diffused lens behind faceplate.
- Wet Location listed for indoor or outdoor use.
- Mounts in a standard single gang box.
- Life span of 50,000 hours L70.
- ELST9330 / ELST9340: 25 lm.
- Input Volt: 12V or 120V. (12V units work with 12V AC or 12V DC supply)
- Rated: IP67.

DIMENSIONS



Back View



Back View

SPECIFICATIONS

Wattage	2W
Voltage	12V · 120V
Color temp.	3000K · 4000K
Lamp type	LED
CRI	90+
Shape	Rectangular

FINISHES



White



Black



Copper



Bronze



Nickel

Item page
elcolighting.com/items/ibis-led-step-light-angled-louver
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

Ibis Collection™

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **Ibis™ LED Step Light with Angled Louver (Horizontal)** item number (Select one) Example: **ELST9330B** Your item number:

ITEM	VOLTAGE	CCT	FINISH
ELST9	**3** 12V **7** 120V	**30** 3000K **40** 4000K	**W** White **B** Black **CP** Copper **BZ** Bronze **N** Nickel

TECHNICAL DETAILS

Optics: Louver face directs light downward to illuminate walkway with frosted lens to diffuse light.

Construction: Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Security screws for mounting faceplate to box included.

Installation: Easily installs into a standard single gang switch box.

Electrical:

•Ambient operating temperature -23°F (-5°C) to 113°F (45°C).

•120V ELST97: Driver input of 120V 50/60Hz connects directly to line voltage power.
•12V ELST93: Input of 12V requires an external transformer. (12V units work with 12V AC or 12V DC supply)

LED Technology:

• 90+ CRI color rendering.
• Lumen Maintenance of 50,000 hours L70 Life.
• LED Array.

Listings: cETLus listed for Wet Location.

Warranty: ELCO Products are built to last. 5-year Limited warranty

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.