ELCO Lighting

Project Name:

Fixture Type:

Date:

KOTO FOCUS™ ARCHITECTURAL LED LIGHT ENGINE

Module

Koto™ Adjustable Beam 18° - 50° Angles. Works with 2", 3", 4", 5" and 6" Architectural Koto Housings and Koto™ Trims



FEATURES

- Includes white snoot installed on module and field changeable black snoot.
- Light engine used with Koto™ Architectural Housings
- See Koto™ Architectural housings for lumen output options
- Driver on housing extends lifespan and allows for more dimming and EM options
- Adjustable Focus: 18° to 50° with a simple twist of the lens
- Works in 2", 3", 4", 5" and 6" ELCO housings with Koto™ twist-&-lock trims
- 95+ CRI color rendering
- Title 24 JA8-2025-E Registered
- Life span of 50,000 hours L70
- Covered by U.S. PATENTS and Patents Pending

DIMENSIONS



SPECIFICATIONS

Wattage	18.9W
Lumens	Up to 1690 lm (18.9W MAX)
Color temp.	2700K · 3000K · 3500K · 4000K
Lamp type	LED
Beam angle	18° - 50°
CRI	95+

Item page
elcolighting.com/items/koto-focus-architectural-led-light-engine
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

4" Architectural Koto™ · 2" Architectural Koto™ · 3" Architectural Koto™ · 6" Architectural Koto™

PRODUCT NUMBER BUILDER

Specify **Koto Focus™ Architectural LED Light Engine** item number (Select one) Example: **ELK2127D-FC** Your item number:

ITEM	LUMENS	CCT	BEAM ANGLE
ELK			
	21 Up to 1690 lm (18.9W MAX)[1]	**27D** 2700K **30D** 3000K **35D** 3500K **40D** 4000K	**-FC** 18° - 50°

No separate code: Lumens: 1360 lm MAX., 1430 lm MAX., 1510 lm MAX., 1690 lm MAX., 1430 lm, 1690 lm

© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

[1] Lumen output varies based on the architectural Koto housing used

TECHNICAL DETAILS

Optics: PC lens diffuses light evenly throughout while reducing glare with LED COB technology.

Construction: Diecast aluminum body with heat fins allow for efficient cooling.

Compatible Housings: Koto™ Module is compatible with Architectural Housings: 120/277V 0-10V/Triac/ELV or 120V Triac/ELV with optional Emergency Battery Backup.

• E3LK65ICA, E3LK66ICAD, E3LK65RICA, ELK72FICA, ELK73FICAD (10W, 250mA) *ELK21 Delivered Lumens:* 2700K: 890 lm, 3000K: 930 lm, 3500K: 990 lm, 4000K: 1020 lm

• E3LK76ICA, E3LK77ICAD, E4LK98ICA, E4LK99ICAD (15W, 350mA) *ELK21 Delivered Lumens:* 2700K:1140 lm, 3000K:1200 lm, 3500K: 1270 lm, 4000K: 1390 lm

• E3LK53ICA, E3LK54ICAD, E4LK47ICA, E4LK48ICAD (17W, 400mA) *ELK21 Delivered Lumens:* 2700K:1220 lm, 3000K:1290 lm, 3500K: 1360 lm, 4000K: 1400 lm

ELK21 Delivered Lumens:

• E3LK85ICAD, E4LK79ICAD (19W, 450mA)

2700K:1360 lm, 3000K:1430 lm, 3500K: 1510 lm, 4000K: 1690 lm

Installation: Twist-lock design for toolless trim installation, for use with Koto™ trims only. Adjustable Focus: 18° to 50° with a simple twist of the lens. Can be used in 2", 3" & 4" Architectural Koto™ Housings only.

LED Technology: Color Rendering Index (CRI) of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Based on housing used. See Koto™ Architectural Housings for options.

Listings: UL Listed (US and Canada) for Damp Locations. UL Listed (US and Canada) for Wet Location with Wet location trims. RoHS Compliant. California Title 24 JA8-2025-E.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.