ELCO Lighting

Project Name:

Fixture Type:

Date:

KOTO FOCUS™ LED MODULE

Module · Round · 1 1/2"

Koto™ Adjustable Beam 18° - 50° Angles. Works with 2", 3", 4" & 6" Recessed Housings and Koto™ Trims



FEATURES

- Integrated 120V Dimmable Driver Triac/ELV
- 95+ CRI color rendering
- Works in 2", 3", 4" & 6" ELCO housings with Koto™ twist-on trims
- Adjustable Focus: 18° to 50° with a simple twist of the lens
- Covered by U.S. PATENTS and Patents Pending

DIMENSIONS



SPECIFICATIONS

Wattage	10.5W
Lumens	770 lm - 860 lm (10.5W)
Voltage	120V
Color temp.	2700K · 3000K · 3500K · 4000K · Sunset
Dimming	Triac/ELV
Lamp type	LED
Beam angle	18° - 50° · Adjustable Beam 18° - 50°
CRI	95+
Aperture	1 1/2"
Shape	Round
Koto™ focus LED module	ELK
Accessory option	Snoot

FINISHES

White

Item page
elcolighting.com/items/koto-focus-led-module
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2" Standard Koto™ · 3" Standard Koto™ · 4" Standard Koto™ · 6" Standard Koto™ · Standard Koto™ Multiples · 5" Standard Koto™ · Koto™ Downsizer Ring

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **Koto Focus™ LED Module** item number (Select one) Example: **ELK0727-FC** Your item number:

ITEM	LUMENS	CCT	BEAM ANGLE
ELK	**07** 770 lm - 860 lm (10.5W)	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[1]	**-FC** 18° - 50° Adjustable Beam 18° - 50°

No separate code: Lumens: 770 lm, 800 lm, 830 lm, 860 lm, 720 lm

[1] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

TECHNICAL DETAILS

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless trim installation, for use with Koto™ trims only. Adjustable Focus: 18° to 50° with a simple twist of the lens. Can be used in 2", 3", 4", and 6" housings with quick connect base.

Electrical: 120V Input Module. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens:

ELK0727 770 lm/2700K **ELK0730** 800 lm/3000K **ELK0735** 830 lm/3500K **ELK0740** 860 lm/4000K

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 5%. For a full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. UL Listed (US and Canada) for Wet Location with Wet location trims. RoHS Compliant. Meets California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.