ELCO Lighting

Project Name:

Fixture Type:

Date:

KOTO™ LED MODULE

Module · Round · 1 1/2″

Works with 2″, 3″, 4″, 5" & 6" Recessed Housings and Koto™ Trims



FEATURES

- Integrated 120V Dimmable Driver Triac/ELV
- 95+ CRI color rendering
- Sunset Module ELK09SD & ELK11SD starts from 3000K and dims to 1800K
- Human Centric Module ELK11HC starts from 4000K and dims to 2200K
- Works in 2″, 3″, 4″ and 6″ ELCO housings with Koto™ twist-on
- Energy Star Certified
- Title 24 JA8-2025-E Compliant
- Standard 38° Lens installed, 25° and 60° lenses included; modules ordered with a beam suffix (-S 18°, -N 25°, -W 60°, -E 90°) come with that lens only - Optional Lens: 18° (EP731C), 90° (EP739C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47), Clear Lens (L48), Frosted Lens (L49), Snoot (L50), Color Shifter (L51), Blue Lens (L52), Pink Lens (L53), Single Asymmetric Lens (L54), Double Asymmetric Lens (L55)
- Covered by U.S. PATENTS and Patents Pending

DIMENSIONS



SPECIFICATIONS

Wattage	10.5 · 12.5 · 5 W
Lumens	350 · 750 · 950 · 1150 · 1350 lm
Voltage	120V
Color temp.	2400K · 2700K · 3000K · 3500K · 4000K · Sunset · Human Centric
Dimming	Triac/ELV
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 90°
CRI	95+
Aperture	1 1/2"
Shape	Round

Item page
elcolighting.com/items/koto-led-module
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ Standard Koto™ · 3″ Standard Koto™ · 4″ Standard Koto™ · 6″ Standard Koto™ · Standard Koto™ Multiples · 5″ Standard Koto™ · Koto™ Downsizer Ring · 4″ Koto™ Sloped Ceiling

⬇ Dimmer compatibility list

elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **Koto™ LED Module** item number (Select one) Example: **ELK0724** Your item number:

ITEM	LUMENS	CCT	BEAM ANGLE
ELK	**07** 750 lm (10.5W) **09** 950 lm (10.5W) **11** 1150 lm **13** 1350 lm **03** 350 lm (5W)	**24** 2400K **27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD** Sunset[1,2] **HC** Human Centric[3,4]	38°[5] **-S** 18° **-N** 25° **-W** 60° **-E** 90°[6]

No separate code: Lumens: 730 lm, 770 lm, 800 lm, 830 lm, 860 lm, 900 lm, 940 lm, 990 lm, 1040 lm, 1100 lm, 1200 lm, 1260 lm, 1250 lm, 1300 lm, 1400 lm, 1050 lm, 1210 lm, 1060 lm

[1] Available with ELK09 and ELK11 lumen outputs only [2] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed [3] Available with ELK11 lumen outputs only [4] Human Centric, Dim to Warm technology, automatically transitions from 4000K to 2200K when dimmed [5] 38° lens installed. Includes 25° and 60° lens with module. [6] 90° Frosted Reflector

DELIVERED LUMENS

ITEM NUMBER	LUMENS	COLOR TEMP.	WATTS	ITEM NUMBER	LUMENS	COLOR TEMP.	WATTS
ELK0724	730 lm	2400K	10.5W	**ELK1124**	1060 lm	2400K	12.5W
ELK0727	770 lm	2700K	10.5W	**ELK1127**	1100 lm	2700K	12.5W
ELK0730	800 lm	3000K	10.5W	**ELK1130**	1150 lm	3000K	12.5W
ELK0735	830 lm	3500K	10.5W	**ELK1135**	1200 lm	3500K	12.5W
ELK0740	860 lm	4000K	10.5W	**ELK1140**	1260 lm	4000K	12.5W
ELK0924	900 lm	2400K	10.5W	**ELK11SD**	1050 lm	Sunset	12.5W
ELK0927	940 lm	2700K	10.5W	**ELK11HC**	1050 lm	Human Centric	12.5W
ELK0930	990 lm	3000K	10.5W	**ELK1327**	1250 lm	2700K	12.5W
ELK0935	1040 lm	3500K	10.5W	**ELK1330**	1300 lm	3000K	12.5W
ELK0940	1100 lm	4000K	10.5W	**ELK1335**	1350 lm	3500K	12.5W
ELK09SD	940 lm	Sunset	10.5W	**ELK1340**	1400 lm	4000K	12.5W

TECHNICAL DETAILS

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology. Standard lens is shatterproof.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist & Lock design for toolless trim installation, for use with Koto™ trims only. Can be used in 2", 3", 4", 5" and 6" housings with quick connect base.

Electrical: 120V Input Module. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Operating Temperature: 0°F - 200°F of operating temperature.

LED Technology: Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 5%. For full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. UL Listed (US and Canada) for Wet Location with Wet location trims. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2025-

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

E standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.